

# HANWHA- Videosecurity screenSMT-2730PV



## DESCRIPTION

## TECHNICAL CHARACTERISTICS

Brand : HANWHA
Part number : **SMT-2730PV
AC input voltage : 110 V
Built-in processor : N
Built-in speaker(s) : N
Card reader integrated : Y
Compatible memory cards : MicroSD (TransFlash), MicroSDHC, MicroSDXC
Computer system : N
Contrast ratio (typical) : 1000:1
Display brightness : 300 cd/m <sup>2</sup>
Display depth : 41.1 mm
Display diagonal : 68.6 cm (27»)
Display height : 413 mm
Display number of colours : 16.78 million colours
Display resolution : 1920 x 1080 pixels
Display technology : LED
Display weight : 8.5 kg
Display width : 620 mm
Ethernet LAN : Y
Ethernet LAN (RJ-45) ports : 1
Ethernet LAN data rates : 10,100 Mbit/s
HD type : Full HD
HDMI input ports quantity : 1
HDMI ports quantity : 1
Native aspect ratio : 16:9
Operating relative humidity (H-H) : 0 - 90%
Operating temperature (T-T) : 0 - 50 °C

Package depth : 194 mm
Package height : 551 mm
Package weight : 11 kg
Package width : 750 mm
Panel life : 30000 h
Placement supported : Indoor
Product colour : Black
Product design : Digital signage flat panel
Purpose : Universal
Response time : 14 ms
Storage relative humidity (H-H) : 0 - 90%
Storage temperature (T-T) : -20 - 60 °C
Touchscreen : N
Viewing angle, horizontal : 178°
Viewing angle, vertical : 178°
Wi-Fi : N