



## DESCRIPTION

## TECHNICAL CHARACTERISTICS

Brand : TP-LINK

Part number : EAP650

### Caractéristiques :

5 GHz : Y

Modulation : 1024-QAM, OFDM

### Design :

Certification : CE, FCC, RoHS

2:4 GHz : Y

AC adapter included : Y

Access Control List (ACL) : Y

Antenna direction type : Omni-directional

Antenna gain level (max) : 5 dBi

Antenna type : Internal

Depth : 160 mm

Ethernet LAN (RJ-45) ports : 1

Ethernet LAN data rates : 10,100,1000 Mbit/s

Frequency band : 2.4 - 5 GHz

Harmonized System (HS) code : 85176990

Height : 33.6 mm

LED indicators : Y

MAC address filtering : Y

Maximum data transfer rate : 2976 Mbit/s

Maximum data transfer rate (2:4 GHz) : 574 Mbit/s

Maximum data transfer rate (5 GHz) : 2402 Mbit/s

MIMO : Y

MIMO type : Multi User MIMO

Networking standards : IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.1x, IEEE 802.3at

Number of products included : 1 pc(s)
Number of SSID supported : 16
Operating relative humidity (H-H) : 10 - 90%
Operating temperature (T-T) : 0 - 40 °C
Output current : 1 A
Output voltage : 12 V
Placement : Ceiling, Wall
Power over Ethernet (PoE) : Y
Product colour : White
Quality of Service (QoS) support : Y
Quick start guide : Y
Rate limiting : Y
Security algorithms : SNMP, SNMPv2, SNMPv3, SSH, WPA-Enterprise, WPA-PSK, WPA2-Enterprise, WPA2-PSK, WPA3-Enterprise, WPA3-PSK
Service Set Identifier (SSID) features : Multiple SSIDs
Spread spectrum method : OFDMA
Storage relative humidity (H-H) : 5 - 90%
Storage temperature (T-T) : -40 - 70 °C
Transmitting power (CE) : <20 dBm(2.4 GHz, EIRP) <23 dBm(5 GHz, Band1 & Band2, EIRP) <30 dBm(5 GHz, Band3, EIRP)
Transmitting power (FCC) : <25 dBm (2.4 GHz) <25 dBm (5 GHz)
VLAN support : Y
Web-based management : Y
Width : 160 mm
Wi-Fi Multimedia (WMM)/(WME) : Y
Wireless isolation : Y