

HANWHA IP camera XND-8080RV



DESCRIPTION

Wisenet X powered by Wisenet 5 network IR indoor vandal dome camera, 5MP @30fps WDR off/on, Motorized Vari-Focal Lens 2.4x (3.9~9.4mm) (92.1°~38.7°), H.265/H.264/MJPEG, WiseStream II compression technology, 120dB WDR, USB port for easy installation, Advanced video analytics and sound classification, High powered IR LEDs range of 98', True D/N, Dual SD card, Hallway view, HLC, Defog detection with simple focus, DIS , 12VDC/PoE, IK08

TECHNICAL CHARACTERISTICS

Brand : HANWHA
Part number : XND-8080RV
Représentation / réalisation :
Type : IP security camera
Réseau :
Bluetooth : N
Connectivité :
Interface : RJ-45
Active tampering alarm : Y
Adjustment shutter speed : Manual
Alarm input/output : Y
Angle of rotation : 355°
Audio system : 2-way
Back Light Compensation (BLC) : Y
Bit rate control : Constant Bit Rate (CBR)/Variable Bit Rate (VBR)
Cabling technology : 10/100Base-T(X)
Camera shutter speed : 2 - 1/12000 s
Camera shutter type : Electronic
Card reader integrated : Y
Compatible memory cards : SD, SDHC, SDXC
Connectivity technology : Wired
Day/night mode : Y
DC output voltage : 12
Diameter : 14.1 cm

Ethernet interface type : Fast Ethernet
Ethernet LAN : Y
Ethernet LAN (RJ-45) ports : 1
Flip & mirror : Y
Focal length range : 3.9 - 9.4 mm
Focus : Motorized/Manual
Fog proof : Y
Form factor : Dome
Frame rate : 30 fps
Height : 113 mm
Highlight Compensation (HLC) : Y
Housing material : Aluminium
HTTPS encryption : Y
IK code : IK08
IP address filtering : Y
Languages support : Simplified Chinese, Traditional Chinese, Czech, German, Dutch, English, Spanish, French, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Turkish
LED type : IR
Lens mount interface : Board mount
Mac compatibility : Y
Mac operating systems supported : Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra
Maximum aperture number : 1.3
Maximum memory card size : 512 GB
Maximum output level : 1 Vpp
Maximum resolution : 2560 x 1920 pixels
Microphone in : Y
Mounting type : Ceiling
Networking standards : IEEE 802.1x, IEEE 802.3af
Night vision : Y
Night vision distance : 30 m
Noise reduction : Y
Number of cameras : 1
Number of effective pixels (H x V) : 2616 x 1976 pixels
Number of users : 20 user(s)
Operating temperature (T-T) : -10 - 55 °C
Optical sensor size : 25.4 / 1.8 mm (1 / 1.8»)
Output impedance : 75
Pan range : 0 - 354°
Placement supported : Indoor
Power consumption (max) : 9 W
Power consumption (Power over Ethernet (PoE)) : 10 W
Power over Ethernet (PoE) : Y
Power source type : PoE
Privacy masking : Y
Product colour : Ivory
Progressive scan : Y
Protection features : Vandal proof
PTZ control : Y
PTZ modes : Digital PTZ
Quality of Service (QoS) support : Y
Sensor type : CMOS
Signal-to-Noise Ratio (SNR) : 50 dB
Storage temperature (T-T) : -50 - 60 °C

Streaming method : Multicast, Unicast
Supported graphics resolutions : 320 x 240, 640 x 360, 640 x 480 (VGA), 720 x 480, 720 x 576, 800 x 448, 800 x 600 (SVGA), 1024 x 768 (XGA), 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1280 x 960, 1600 x 1200 (UXGA), 1920 x 1080 (HD 1080), 2560 x 1440, 2560 x 1920
Supported network protocols : TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, PPPoE, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, PIM-SM, UPnP, Bonjour
Tilt angle range : 0 - 67°
USB connectivity : Y
Video compression formats : H.264, H.265, M-JPEG, MPEG4
Video motion detection : Y
Video streaming : Y
Voice codecs : G.711, G.726
Weight : 732 g
White balance : ATW, AWC, Indoor, Manual, Mercury lamp, Outdoor, Sodium lamp
Wide Dynamic Range (WDR) : Y
Wi-Fi : N
Windows operating systems supported : Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 Pro, Windows 10 Pro x64, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Wind