



DESCRIPTION

Captivate your audience

With an ultra large screen experience

Experience your content like never before thanks to four times the resolution of a conventional display. This ultra large 75 display offers 3840 x 2160 pixels so refined, so lifelike, it's a window to a new world

Optimized for public viewing

- 4K Ultra HD: resolution like you've never seen it before

Innovative solutions for any signage application

- Play content from 4 separate inputs with QuadViewer
- CMND: Take control of your displays
- Optional OPS Insert to create an all-in-one solution
- Schedule what you want, when you want with SmartPlayer

Care about you, your business and your audience

- SmartPower for energy saving
- Keep your content up and running with FailOver
- Simplify meetings with FailOver for conferencing

TECHNICAL CHARACTERISTICS

Brand : PHILIPS

Part number : 75BDL3000U/00

Connectivité :

RS-232C : Y

Certificat :

Certification : CE, UL/cUL, CCC, C-Tick, GOST, FCC, Class A

AC input frequency : 50 - 60 Hz

AC input voltage : 100 - 240 V

Audio formats supported : AAC, AIFF, ASF, LPCM, M4A, MP3, MP4, WAV, WMA

AUX in : Y

Batteries included : Y
Bezel width (bottom) : 1.25 cm
Bezel width (side) : 1.25 cm
Bezel width (top) : 1.25 cm
Built-in speaker(s) : Y
Cables included : AC, HDMI, RS-232
Component video (YPbPr/YCbCr) in : 1
Composite video in : 1
Contrast ratio (dynamic) : 500000:1
Contrast ratio (typical) : 1200:1
Depth : 73.8 mm
Display brightness : 410 cd/m ²
Display diagonal : 189.2 cm (74.5»)
Display diagonal (metric) : 189.3 cm
Display number of colours : 1.073 billion colours
Display resolution : 3840 x 2160 pixels
Display technology : LED
DisplayPorts quantity : 2
DVI port : Y
DVI-D ports quantity : 1
Ethernet LAN : Y
Ethernet LAN (RJ-45) ports : 1
HD type : 4K Ultra HD
HDMI ports quantity : 3
Height : 955 mm
Image formats supported : BMP, GIF, JPEG, JPG
LED backlighting type : Edge-LED
Manual : Y
Native aspect ratio : 16:9
Number of built-in speakers : 2
On Screen Display (OSD) : Y
On Screen Display (OSD) languages : Arabic, Simplified Chinese, Traditional Chinese, German, English, Spanish, French, Italian, Japanese, Polish, Portuguese, Russian, Turkish
Operating altitude : 0 - 3000 m
Operating relative humidity (H-H) : 20 - 80%
Operating temperature (T-T) : 5 - 40 °C
Orientation : Horizontal
Panel mounting interface : 600 x 400 mm
Panel type : IPS
Picture-in-Picture : Y
Pixel pitch : 0.429 x 0.429 mm
Power consumption (standby) : 0.5 W
Power consumption (typical) : 197 W
Product colour : Black
Product design : Digital signage flat panel
Quick start guide : Y
Remote (IR) input : 1
Remote (IR) output : 1
Remote control included : Y
Response time : 8 ms
RMS rated power : 20 W
Storage temperature (T-T) : -20 - 60 °C
Sustainability certificates : RoHS

Touchscreen : N

TV tuner integrated : N

VESA mounting : Y

VGA (D-Sub) input ports : 1

Video formats supported : M2TS, M4V, MKV, MP4, MPEG, MPG, MTS, TS, VOB, WMV

Viewing angle, horizontal : 178°

Viewing angle, vertical : 178°

Weight : 53.3 kg

Width : 1676.6 mm