

EPDU BA 0U (309 16A 3P)21XC13:3XC19



DESCRIPTION

Designed for reliable and cost effective power distribution, the ePDU G3 Basic models feature Eatons patented IEC outlet grip plug retention, color-coded outlet sections, a low-profile form factor and a high operating temperature. 0U models include both rear and side button mounting system and Eatons patented variable mounting system.

TECHNICAL CHARACTERISTICS

Brand : EATON

Part number : EBAB20

Design :

Type : Three-phase

Caractéristiques :

Certification : CB, CE, EN 60950-1:2006/A11:2009/A1:2010/A12:2011\nIEC 60950-1, EN 61000-6-2:2005\nEN 61000-6-4:2007+A1:2011\nEN 50581 : 2012, REACH, WEEE\nISO 9001:2008 / ISO 14001:2004

AC input frequency : 50 Hz

AC outlet types : C13 coupler, C19 coupler

AC outlets quantity : 24 AC outlet(s)

Cable colour : Black

Cable length : 3 m

Cables included : LAN (RJ-45)

Depth : 53 mm

Dimensions (WxDxH) : 52 x 53 x 1070 mm

Firmware upgradeable : Y

Firmware upgradeable via : Network, USB

Form factor : Rackmount

Height : 1070 mm

LED indicators : Y

Management protocols : SNMP, Telnet

Maximum current : 16 A

Maximum input current per phase : 16 A

Maximum power : 11000 W

Mounting : Vertical

Nominal input voltage : 400 V

Nominal output voltage : 230 V

Operating temperature (T-T) : 0 - 60 °C

Output connections : 21 x C13 & 3 x C19

Package depth : 214 mm

Package height : 1200 mm

Package width : 200 mm

PDU types : Basic

Power plug : IEC 60309

Product colour : Black

Rack capacity : 0U

Rack mount kit : Y

Rack mounting : Y

Sustainability certificates : RoHS

Weight : 2.2 kg

Width : 52 mm