

# EPDU IL 0U (309 16A 1P)1X309



## DESCRIPTION

New ePDU G3 In-Line Metered Input models upgrade existing basic installation to include, including  $\pm 1\%$  billing grade accuracy, an advanced LCD pixel display, a hot-swap meter and the ability to daisy chain four ePDUs to share the same network connection and IP address.

## TECHNICAL CHARACTERISTICS

Brand : EATON

Part number : EILB13

### Design :

Type : Single-phase

AC input frequency : 50 Hz

AC outlet types : IEC 60309

AC outlets quantity : 1 AC outlet(s)

Cable colour : Black

Cable length : 3 m

Cables included : LAN (RJ-45)

Depth : 311 mm

Dimensions (WxDxH) : 52 x 311 x 53 mm

Display : LCD

Ethernet LAN (RJ-45) ports : 1

Firmware upgradeable : Y

Firmware upgradeable via : Network, USB

Form factor : Rackmount

Height : 53 mm

LED indicators : Y

Management protocols : SNMP, Telnet

Maximum current : 16 A

Maximum input current per phase : 16 A

Maximum power : 3700 W

Mounting : Vertical

Nominal input voltage : 230 V

Nominal output voltage : 230 V
Operating temperature (T-T) : 0 - 60 °C
Output connections : 1 x IEC 309
Package weight : 2.82 kg
PDU types : Metered
Power plug : IEC 60309
Product colour : Black
Rack capacity : 0U
Rack mount kit : Y
Rack mounting : Y
Sustainability certificates : RoHS
Weight : 1.82 kg
Width : 52 mm