



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : PHILIPS
Part number : 65BDL6005X/00
Certificat :
Certification : FCC, Class A CB ETL
Batteries included : Y
Bezel width : 2.3 mm
Built-in processor : N
Built-in speaker(s) : Y
Cables included : AC, DisplayPort, IR sensor, LAN (RJ-45)
Computer system : N
Contrast ratio (dynamic) : 500000:1
Contrast ratio (typical) : 1300:1
Depth : 88.8 mm
Display brightness : 500 cd/m²
Display diagonal : 165.1 cm (65»)
Display diagonal (metric) : 164 cm
Display number of colours : 1.07 billion colours
Display resolution : 3840 x 2160 pixels
Display technology : LED
DisplayPort version : 1.2
DisplayPorts in : 1
DisplayPorts out : 1
DisplayPorts quantity : 2
DVI port : Y
DVI-D ports quantity : 1
Energy saving functions : Smart Power
Ethernet LAN : Y

Haze rate : 25%
HD type : 4K Ultra HD
HDMI input ports quantity : 2
HDMI ports quantity : 2
HDMI version : 2.0
Height : 807.6 mm
LED backlighting type : Direct-LED
Mean time between failures (MTBF) : 50000 h
Native aspect ratio : 16:9
Native refresh rate : 60 Hz
Number of built-in speakers : 2
Number of OSD languages : 12
Number of speaker outputs : 1
On Screen Display (OSD) : Y
On Screen Display (OSD) languages : Arabic, Simplified Chinese, Traditional Chinese, German, English, Spanish, French, Italian, Japanese, Polish, Russian, Turkish
Open Pluggable Specification (OPS) : Y
Operating altitude : 0 - 3000 m
Operating relative humidity (H-H) : 20 - 80%
Operating temperature (T-T) : 0 - 40 °C
Orientation : Horizontal/Vertical
Panel mounting interface : 100 x 100 mm
Pixel pitch : 0.372 x 0.372 mm
Placement supported : Indoor
Power consumption (max) : 400 W
Power consumption (standby) : 0.5 W
Power consumption (typical) : 210 W
Product colour : Black
Product design : Digital signage flat panel
Purpose : Universal
Quick start guide : Y
Remote (IR) input : 1
Remote (IR) output : 1
Remote control included : Y
Response time : 8 ms
RMS rated power : 20 W
RS-232 interface : Y
Screen saving functions : Y
Set depth (inch) : 8.89 cm (3.5»)
Set height (inch) : 80.8 cm (31.8»)
Set width (inch) : 143.3 cm (56.4»)
Signal loop through : DisplayPort, LAN, IR and RS232 via RJ45
Storage relative humidity (H-H) : 5 - 95%
Storage temperature (T-T) : -20 - 60 °C
Sustainability certificates : CE, RoHS
Sustainability compliance : Y
Tiled Matrix : Up to 10 x 10
Touchscreen : N
USB port : Y
USB ports quantity : 1
USB version : 2.0
VESA mounting : Y
VGA (D-Sub) input ports : 1
Viewing angle, horizontal : 178°

Viewing angle, vertical : 178°
Wall mountable : Y
Warranty period : 3 year(s)
Width : 1432.6 mm
Wi-Fi : N