

NETIS ST31055 Fast Ethernet Switch+ Plastic Case- 5 Ports



DESCRIPTION

The NETIS ST3108S has 5 x 10/100 Mbps ports. The price is as compact as the size, for a reliable and efficient Fast Ethernet device.

The switch supports N-way and Auto MDI/MDI-X functions, detecting and adapting the MDI or MDI-X configuration to match the other end of the link.

In addition, the Energy-Efficient Ethernet technology reduces the power consumption when the activity is low.

Product features:

- 5 x 10/100 Mbps RJ-45 ports with auto negotiation and MDI/ MDI-X functions
- Compliant with the following standards: IEEE 802.3 10Base-T, IEEE 802.3u 100Base-TX
- IEEE802.3x flow control in Full Duplex
- Data transmission rates: 10/100Mbps in Half-Duplex, 20/200Mbps in Full-Duplex
- 2 K MAC address table
- Housing: black ABS/ can be wall-mounted
- Dimensions: 130 x 70 x 21mm
- Weight: 75 g
- External power supply: 110/230 V, 5V 800 mA, 5.5/2.1mm jack
- Supported temperature in operation: 0°~40°C
- Supported humidity rate in operation: 5~90% without condensing

TECHNICAL CHARACTERISTICS

Brand : STONET BY NETIS
Part number : ST3105C
Main features :
Network standard : 10/100 Mbps
ODI Model Layer : Unmanaged
Management : No
Operating environment : Soho
Industrial : No

Rackmount : No
PoE function : No
Power supply : External power adapter included
Outband console port : No
Temperature supported in operation : 0 to 50°C
Mounting system : Wallmounted
Connectors :
Total number of ports : 5
Number of RJ-45 ports : 5
Number of fiber ports : 0
Number of BNC Ethernet ports : 0
Other ports : No
RJ-45 patch cords :
Number of 10/100 ports : 5
Number of 10G ports : 0
Number of Gigabit ports : 0
Fiber optics :
Number of 100FX ports : 0
Number of SFP Gigabit ports : 0
Number of SFP+ ports : 0
Number of SFP 1G/100 ports : 0
Number of SFP 100FX ports : 0
PoE data :
PoE standard : -
PoE budget (Watts) : 0
Number of 15-Watt PoE ports : 0
Number of 30-Watt PoE+ ports : 0
Number of 60-W PoE++ ports : 0
Dimensions :
Length (mm) : 88
Width (mm) : 63
Height (mm) : 20