

93PS-10(20)-15-0-MBS-6



DESCRIPTION

The Eaton 93PS provides the lowest Total Cost of Ownership and maximum availability in its power range. Providing top of the line efficiency and resiliency, its the perfect choice for small data centers and mission critical applications.

TECHNICAL CHARACTERISTICS

| |
|---|
| Brand : EATON |
| Part number : BA01A0306A01100000 |
| Design : |
| Certification : IEC 62040-2 IEC 62040-3 |
| Depth : 750 mm |
| Display type : LCD |
| Efficiency : 96% |
| Form factor : Tower |
| Height : 1300 mm |
| Hot-swap battery : Y |
| Input frequency : 50/60 Hz |
| Input operation voltage (max) : 415 V |
| Input operation voltage (min) : 220 V |
| International Protection (IP) code : IP20 |
| LED indicators : Y |
| Number of batteries supported : 64 |
| Number of input phases : 3 |
| Number of output phases : 3 |
| Output frequency : 50/60 Hz |
| Output operation voltage (max) : 415 V |
| Output operation voltage (min) : 220 V |
| Output power : 10000 W |
| Output power capacity : 10 kVA |
| Output power factor : 1 |
| Power protection features : Overload |
| Product colour : Black |

Safety : IEC 62040-1

UPS topology : Double-conversion (Online)

Width : 335 mm