

Eaton 9SX 1000i



DESCRIPTION

The Eaton 9SX UPS offers high availability, flexibility and advanced protection for infrastructure, industrial, medical, IT, networking, storage and telecom. Delivering on-line double conversion protection in versatile Rack/Tower format with up to 95% efficiency.

TECHNICAL CHARACTERISTICS

Brand : EATON
Part number : 9SX1000I
Design :
Certification : IEC/EN 62040-1, UL 1778, CSA 22.2, IEC/EN 62040 -2 , FCC Class B, CISPR22 Class B, CE /CB report (TUV) / cULus / EAC / RCM / BIS / KCC
AC outlet types : C13 coupler
AC outlets quantity : 6 AC outlet(s)
Automatic battery test : Y
Battery technology : Sealed Lead Acid (VRLA)
Bundled software : Intelligent Power Software suite
Depth : 387 mm
Display type : LCD
ECO mode : N
Form factor : Tower
Harmonized System (HS) code : 85078000
Height : 252 mm
Hot-swap battery : Y
Input connection type : IEC C14
Input frequency : 40/70 Hz
Input operation voltage (max) : 276 V
Input operation voltage (min) : 190 V
Management card included : N
Noise level : 41 dB
Nominal input voltage : 230 V
Nominal output voltage : 230 V
Number of input phases : 1
Number of output phases : 1

Operating temperature (T-T) : 0 - 40 °C
Output frequency : 50/60 Hz
Output operation voltage (max) : 240 V
Output operation voltage (min) : 200 V
Output power : 900 W
Output power capacity : 1 kVA
Power factor : 0.9
Power plug : C14 coupler
Product colour : Black
RS-232 ports : 1
Safety : IEC/EN 62040-1, UL 1778, CSA 22.2
Serial interface : Y
Serial interface type : RS-232
Typical backup time at half load : 16.5 min
UPS topology : Double-conversion (Online)
USB 2:0 ports quantity : 1
USB port : Y
Waveform : Pure sine
Weight : 14.8 kg
Width : 160 mm