

HANWHA- 2 Mps 32x Zoom Network PTZ Camera

QNP-6320



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : HANWHA
Part number : QNP-6320
Réseau :
Bluetooth : N
Système d'objectif :
Auto focus : Y
Alarm input/output : Y
Back Light Compensation (BLC) : Y
Bit rate control : Constant Bit Rate (CBR)/Variable Bit Rate (VBR)
Built-in HDD : N
Camera pan control : Y
Camera shutter speed : 2 - 1/12000 s
Camera tilt control : Y
Card reader integrated : Y
Closest focusing distance : 1.5 m
Compatible memory cards : MicroSD (TransFlash), MicroSDHC, MicroSDXC
Day/night mode : Y
Ethernet interface type : Fast Ethernet
Ethernet LAN : Y
Flash memory : 256 MB
Flip & mirror : Y
Focal length range : 4.44 - 142.6 mm
Frame rate : 60 fps
Highlight Compensation (HLC) : Y
HTTPS encryption : Y
Image stabilizer : Y
Infrared (IR) cut-off filter : Y

Internal memory : 1024 MB
IP address filtering : Y
Lens viewing angle, horizontal : 64.66°
Lens viewing angle, vertical : 38.08°
Maximum aperture number : 4.4
Maximum memory card size : 256 GB
Maximum resolution : 1920 x 1080 pixels
Minimum aperture number : 1.6
Minimum illumination : 0.005 lx
Networking standards : IEEE 802.1x
Noise reduction : Y
Number of cameras : 1
Number of lenses : 1
Number of sensors : 1
Number of users : 128 user(s)
Operating relative humidity (H-H) : 0 - 95%
Operating temperature (T-T) : -10 - 55 °C
Optical sensor size : 25.4 / 2.8 mm (1 / 2.8»)
Optical zoom : 32x
Pan preset speed : 700 °/sec
Pan range : 0 - 360°
Pan speed : 200 °/sec
Privacy masking : Y
Quality of Service (QoS) support : Y
Security algorithms : EAP-PEAP, EAP-TLS
Sensor type : CMOS
Storage relative humidity (H-H) : 0 - 95%
Storage temperature (T-T) : -30 - 60 °C
Streaming method : Multicast, Unicast
Supported graphics resolutions : 320 x 240, 640 x 360, 640 x 480 (VGA), 720 x 480, 720 x 576, 800 x 448, 800 x 600 (SVGA), 1024 x 768 (XGA), 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1280 x 960, 1920 x 1080 (HD 1080)
Supported network protocols : IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP,RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, PIM-SM, UPnP, Bonjour, LLDP, SRTP
Tilt angle range : -15 - 90°
Tilt speed : 300 °/sec
Total megapixels : 2 MP
Video compression formats : H.264, H.265, M-JPEG
Video motion detection : Y
Video streaming : Y
Voice codecs : G.711, G.711ulaw, G.726
White balance : ATW, AWC, Indoor, Manual, Mercury lamp, Outdoor, Sodium lamp
Wide Dynamic Range (WDR) : Y
Wi-Fi : N
Zoom capability : Y