

HANWHA IP camera XNV-L6080R



DESCRIPTION

Wisenet X powered by Wisenet 5 network outdoor vandal dome camera, 2MP, Full HD(1080p) @60fps, motorized vari-focal lens 3.1x (3.2~10mm) (109°~33.2°), triple codec H.265/H.264/MJPEG with WiseStream II technology, 120dB WDR, USB port for easy installation, high powered IR LEDs range of 98.43', true D/N, single SD card, hallway view, HLC, defog detection, DIS, PoE, IP66, IK10, -40°C ~ +55°C (-40°F ~ +131°F)

TECHNICAL CHARACTERISTICS

Brand : HANWHA
Part number : XNV-L6080R
Représentation / réalisation :
Type : IP security camera
Réseau :
Bluetooth : N
Vidéo :
Full HD : Y
3D NR (Noise Reduction) : Y
Active tampering alarm : Y
Alert notification type : E-mail
Angle of rotation : 355°
Back Light Compensation (BLC) : Y
Bit rate control : Constant Bit Rate (CBR)/Variable Bit Rate (VBR)
Built-in HDD : N
Cabling technology : 10/100Base-T(X)
Camera shutter speed : 2 ~ 1/12000 s
Camera shutter type : Electronic
Card reader integrated : Y
Compatible memory cards : SD, SDHC, SDXC
Composite video out : 1
Connectivity technology : Wired
Day/night mode : Y
Detect distance : 0.5 m

Diameter : 16 cm
Digital zoom : 24x
Ethernet interface type : Fast Ethernet
Ethernet LAN : Y
Ethernet LAN (RJ-45) ports : 1
Flip & mirror : Y
Focal length range : 3.2 - 11 mm
Focus : Motorized/Manual
Fog proof : Y
Form factor : Dome
Frame rate : 60 fps
Highlight Compensation (HLC) : Y
Housing material : Aluminium
IK code : IK10
Image quality adjustment : Contrast
Image stabilizer : Y
Infrared (IR) cut-off filter : Y
International Protection (IP) code : IP66
IP address filtering : Y
Languages support : Multi
LED type : IR
Length : 118.5 mm
Lens viewing angle, diagonal : 132°
Lens viewing angle, horizontal : 109°
Lens viewing angle, vertical : 57.4°
Mac compatibility : Y
Mac operating systems supported : Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra
Management software : SmartViewer, SSM
Maximum aperture number : 1.6
Maximum memory card size : 256 GB
Maximum resolution : 1920 x 1080 pixels
Mounting type : Ceiling
Networking standards : IEEE 802.1x, IEEE 802.3af
Night vision : Y
Night vision distance : 30 m
Noise reduction : Y
Number of cameras : 1
Number of effective pixels (H x V) : 1945 x 1097 pixels
Number of languages : 17
Number of lenses : 1
Number of sensors : 1
Number of users : 20 user(s)
Operating relative humidity (H-H) : 0 - 90%
Operating temperature (T-T) : -40 - 55 °C
Optical sensor size : 25.4 / 2.8 mm (1 / 2.8»)
Optical zoom : 3.1x
Pan range : 0 - 354°
Placement supported : Indoor & outdoor
Power consumption (max) : 11 W
Power consumption (typical) : 5 W
Power source type : PoE
Privacy masking : Y
Product colour : Ivory

Progressive scan : Y
PTZ control : Y
Quality of Service (QoS) support : Y
Remotely operated : Y
Security algorithms : EAP-TLS, HTTPS, LEAP
Sensor type : CMOS
Signal-to-Noise Ratio (SNR) : 50 dB
Storage relative humidity (H-H) : 0 - 90%
Storage temperature (T-T) : -50 - 60 °C
Streaming method : Multicast, Unicast
Supported graphics resolutions : 320 x 240, 640 x 360, 640 x 480 (VGA), 720 x 480, 720 x 576, 800 x 448, 800 x 600 (SVGA), 1024 x 768 (XGA), 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1280 x 960, 1920 x 1080 (HD 1080)
Supported network protocols : TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP,RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, PPPoE, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, UPnP, Bonjour
Supported video modes : 1080p
Text caption overlay : Y
Tilt angle range : 0 - 67°
Total megapixels : 2 MP
USB port : Y
Video compression formats : H.264, H.265, M-JPEG, MPEG4
Video motion detection : Y
Video streaming : Y
Web browser : Y
Web-based management : Y
Weight : 940 g
White balance : ATW, AWC, Indoor, Manual, Mercury lamp, Outdoor, Sodium lamp
Wide Dynamic Range (WDR) : Y
Wi-Fi : N
Windows operating systems supported : Window