

HANWHA- Camera QNO-7022R



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : HANWHA
Part number : QNO-7022R
Représentation / réalisation :
Type : IP security camera
Réseau :
Bluetooth : N
Alarm input/output : Y
Alert notification type : E-mail
Anti-flicker : Y
Bit rate control : Constant Bit Rate (CBR)/Variable Bit Rate (VBR)
Built-in HDD : N
Camera pan control : N
Camera shutter type : Electronic
Camera tilt control : N
Card reader integrated : Y
Compatible memory cards : MicroSD (TransFlash), MicroSDHC, MicroSDXC
Connectivity technology : Wired
Day/night mode : Y
DC output voltage : 12
Detect distance : 63 m
Diameter : 7 cm
Ethernet interface type : Fast Ethernet
Ethernet LAN : Y
Ethernet LAN (RJ-45) ports : 1
Flash memory : 256 MB
Flip & mirror : Y
Focal length range : 4 mm

Form factor : Bullet
Frame rate : 30 fps
Housing material : Aluminium
HTTPS encryption : Y
Identify distance : 6.3 m
IK code : IK10
International Protection (IP) code : IP66
IP address filtering : Y
LED type : IR
Length : 246 mm
Lens viewing angle, diagonal : 92°
Lens viewing angle, horizontal : 78.2°
Lens viewing angle, vertical : 41.2°
Maximum aperture number : 1.6
Maximum memory card size : 128 GB
Maximum resolution : 2560 x 1440 pixels
Mirror : Y
Mounting type : Ceiling/wall
Networking standards : IEEE 802.1x
Night vision : Y
Night vision distance : 25 m
Noise reduction : Y
Number of cameras : 1
Number of lenses : 1
Number of sensors : 1
Number of users : 6 user(s)
Observe distance : 25.2 m
Operating relative humidity (H-H) : 0 - 95%
Operating temperature (T-T) : -40 - 55 °C
Optical sensor size : 25.4 / 3 mm (1 / 3»)
Password protection : Y
Password protection type : User
Placement supported : Outdoor
Power consumption (Power over Ethernet (PoE)) : 10.7 W
Power consumption (typical) : 8 W
Power source type : DC, PoE
Privacy masking : Y
Product colour : Grey
Quality of Service (QoS) support : Y
Recognize distance : 12.6 m
Sample rate : 8 kHz
Security algorithms : HTTPS, SNMPv2, SNMPv3
Sensor type : CMOS
Storage relative humidity (H-H) : 0 - 95%
Storage temperature (T-T) : -40 - 60 °C
Streaming method : Multicast, Unicast
Supported graphics resolutions : 320 x 240, 640 x 480 (VGA), 720 x 480, 800 x 448, 800 x 480 (WVGA), 800 x 600 (SVGA), 1280 x 720 (HD 720), 1280 x 960, 1920 x 1080 (HD 1080), 2560 x 1440
Supported network protocols : IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, PPPoE, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, PIM-SM, UPnP, Bonjour, LLDP
Total megapixels : 4 MP
Video compression formats : H.264, H.265, M-JPEG
Video formats supported : H.264, H.265, M-JPEG

Video motion detection : Y
Video streaming : Y
Voice codecs : G.711, G.711ulaw, G.726
Weight : 700 g
White balance : ATW, AWC, Indoor, Manual, Outdoor
Wide Dynamic Range (WDR) : Y
Wi-Fi : N