

Tp-link Archer C80 Router WiFi 5 AC1900 Gigabit MU-MIMO



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : TP-LINK
Part number : ARCHER C80
Sécurité :
Stateful Packet Inspection (SPI) : Y
Réseaux mobiles :
3G : N
4G : N
Réseau :
Dynamic DNS (DDNS) : Y
Connexion WAN :
Ethernet WAN : Y
Caractéristiques :
Certification : CE, FCC, RoHS
AC adapter included : Y
Access Control List (ACL) : Y
Antenna design : External
Antennas quantity : 4
Browser supported : Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0
Cables included : AC, LAN (RJ-45)
Cabling technology : 10/100/1000Base-T(X)
DC-in jack : Y
Depth : 125 mm
Detachable antenna(s) : Y
DHCP client : Y
DHCP server : Y
DMZ support : Y
Ethernet LAN : Y

Ethernet LAN (RJ-45) ports : 5
Ethernet LAN data rates : 10,100,1000 Mbit/s
Ethernet LAN interface type : Gigabit Ethernet
Firewall : Y
Guest access : Y
Harmonized System (HS) code : 85176990
Height : 30 mm
LED indicators : LAN, Power, Status, WLAN, WPS
Linux operating systems supported : Y
MAC address filtering : Y
Mac compatibility : Y
Mac operating systems supported : macOS
Memory card slot(s) : N
Mobile network generation : 4G
Networking standards : IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
On/off switch : Y
Operating relative humidity (H-H) : 10 - 90%
Operating temperature (T-T) : 0 - 40 °C
Output voltage : 12 V
Package depth : 240 mm
Package height : 82 mm
Package weight : 800 g
Package width : 350 mm
Port forwarding : Y
Power source type : DC
Product colour : Black
Product type : Tabletop router
Quick installation guide : Y
Receiver sensitivity : 5 GHz: 11a 6Mbps:-98dBm, 11a 54Mbps:-78dBm, 11ac VHT20_MCS0:-98dBm, 11ac VHT20_MCS8:-72dBm 11ac VHT40_MCS0:-92dBm, 11ac VHT40_MCS9:-68dBm 11ac VHT80_MCS0:-89dBm, 11ac VHT80_MCS9:-64dBm 2.4 GHz: 11g 6Mbps:-97dBm, 11a 54Mbps:-77dBm 11n VHT20_MCS0:-97dBm, 11n VHT20_MCS8:-72dBm 11n VHT40_MCS0:-92dBm, 11n VHT40_MCS9:-67dBm
Reset button : Y
Security algorithms : 64-bit WEP, 128-bit WEP, WPA, WPA-PSK, WPA2, WPA2-PSK
SIM card slot : N
Storage relative humidity (H-H) : 5 - 90%
Storage temperature (T-T) : -40 - 70 °C
Top Wi-Fi standard : Wi-Fi 5 (802.11ac)
Transmit power : CE: <20dBm(2.4 GHz), <23dBm(5.15 GHz~5.25 GHz), FCC:<30dBm(2.4 GHz & 5 GHz)
Universal Plug and Play (UPnP) : Y
USB port : N
Wall mountable : Y
WAN connection type : RJ-45
Width : 215 mm
Wi-Fi band : Dual-band (2.4 GHz / 5 GHz)
Wi-Fi standards : 802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac)
Windows operating systems supported : Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core, Windows 10 Pro, Windows 10 Pro x64, Windows 10 x64, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 7 x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64, Windows 98SE, Windows NT, Windows Vista, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows Vista x64, Windows XP, Windows XP Home, Windows XP Home x64, Windows XP Professional,

Windows XP Professional x64

WLAN data transfer rate (first band) : 600 Mbit/s

WLAN data transfer rate (max) : 1300 Mbit/s

WLAN data transfer rate (second band) : 1300 Mbit/s

WPS push button