

BOSCH NBN-73013-BA



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : BOSCH

Part number : NBN-73013-BA

Représentation / réalisation :

Type : IP security camera

Alarm input/output : Y

Analog signal format system : NTSC, PAL

Audio codecs : G.711, L16, AAC-LC

Audio input channels : 1

Audio output channels : 1 channels

Audio system full duplex : Y

Built-in HDD : N

Camera shutter speed : 1/25 - 1/15000 s

Camera shutter type : Electronic

Card reader integrated : Y

Compatible memory cards : MicroSDHC, MicroSDXC

Connectivity technology : Wired

Day/night mode : Y

DC output voltage : 12

Ethernet interface type : Fast Ethernet

Ethernet LAN : Y

Firmware upgradeable : Y

Flip & mirror : Y

Form factor : Bullet

Frame rate : 60 fps

Image quality adjustment : Brightness, Contrast, Saturation

Maximum memory card size : 2000 GB

Maximum resolution : 1920 x 1080 pixels

Mounting type : Ceiling/wall
Networking standards : IEEE 802.3at
Noise reduction : Y
Number of cameras : 1
Number of effective pixels (H x V) : 1920 x 1080 pixels
Number of sensors : 1
Optical sensor size : 25.4 / 2.8 mm (1 / 2.8»)
Placement supported : Indoor & outdoor
Power consumption : 600 mA
Power consumption (max) : 7.2 W
Power source type : DC, PoE
Privacy masking : Y
Product colour : Black, Grey
PTZ control : Y
Quality of Service (QoS) support : Y
Region of Interest (ROI) encoding : Y
Reset button : Y
Sensor type : CMOS
Signal-to-Noise Ratio (SNR) : 55 dB
Supported network protocols : IPv4, IPv6, UDP, TCP, HTTP, HTTPS, RTP/RTCP, IGMP V2/V3, ICMP, ICMPv6, RTSP, FTP, ARP, DHCP, APIPA (Auto-IP, link local address), NTP (SNTP), SNMP (V1, V3, MIB-II), 802.1x, DNS, DNSv6, DDNS (DynDNS.org, selfHOST.de, noip.com), SMTP, iSCSI, UPnP (SSDP), DiffServ (QoS), LLDP, SOAP, Dropbox, CHAP
Supported video modes : 720p, 1080p
Video compression formats : H.264, M-JPEG
Video streaming : Y
Web browser : Y
Web-based management : Y
White balance : Auto, Manual
Wide Dynamic Range (WDR) : Y