

ATEN PE1216 VERTICAL ZeroU PDU 16 PORT IP-READY



DESCRIPTION

The ATEN PE1216 Energy PDU contains 16 AC outlets and is available in IEC socket configurations. The ATEN PE1216 Energy PDU features a space-saving 0U design that allows it to be mounted vertically on the outside of a rack, resulting in a more efficient use of space in the server room, while providing 16 AC outlets. The PE1216 Energy PDU should be integrated into an installation with the EC1000 Energy Box, allowing you to monitor the real-time current and environmental conditions of the Energy PDU from the front panel of the EC1000 at the rack, or via Web GUI remotely, making your server room efficiently green with ease.

Specifications :

- Power Outlets Direct : 16 x IEC C13
- Connectors Inlet : 1 x IEC60320 C20
- Energy Sensor Port : 1 x RJ-45 Female
- Nominal Input Power : 100-240V~, 50/60Hz, 16A(Max)
- Nominal Output Power : 100-240V~,50/60Hz Per Outlet 10A (Max) - Total : 16A(Max)
- Physical Properties : Housing Metal - 1.23 kg
- Dimensions : 680 x 44 x 44 mm

Package Contents

- 1x PE1216 Energy PDU
- 1x Power Cord (310 cm - Seperate cable with power connectors C19 and C20)
- 1x Mounting Kit
- 1x User Instructions

TECHNICAL CHARACTERISTICS

Brand : ATEN
Part number : PE1216G-AX-G
Caractéristiques :
Certification : CE, C-Tick, TUV-CB, GOST
AC input frequency : 50 - 60 Hz
AC outlet types : C13 coupler

AC outlets quantity : 16 AC outlet(s)
Cable length : 3 m
Cables included : AC
Depth : 730 mm
Ethernet LAN (RJ-45) ports : 1
Height : 44 mm
Housing material : Metal
Manual : Y
Master (outer) case gross weight : 4.85 kg
Master (outer) case height : 127 mm
Master (outer) case length : 806 mm
Master (outer) case net weight : 3.76 kg
Master (outer) case width : 203 mm
Maximum current : 16 A
Nominal input voltage : 100-240 V
Nominal output voltage : 100 - 240 V
Operating relative humidity (H-H) : 0 - 80%
Operating temperature (T-T) : 0 - 50 °C
Package depth : 790 mm
Package height : 109 mm
Package weight : 2.18 kg
Package width : 90 mm
PDU types : Metered
Power plug : C20 coupler
Product colour : Black
Products per master (outer) case : 2 pc(s)
Storage relative humidity (H-H) : 0 - 80%
Storage temperature (T-T) : -20 - 60 °C
Weight : 1.88 kg
Width : 44 mm