

BOSCH NIN-70122-F1AS



DESCRIPTION

- 12MP / 30 fps sensor for fine details with smooth motion
- Edge or client-side dewarping for easy integration
- Intelligent Video Analytics on full panoramic overview
- Discreet and aesthetic, low-profile design
- Easy twist-click installation

TECHNICAL CHARACTERISTICS

Brand : BOSCH
Part number : NIN-70122-F1AS
Représentation / réalisation :
Type : IP security camera
Détails techniques :
Iris : Y
4G standard : Not supported
Adjustment shutter speed : Auto
Back Light Compensation (BLC) : Y
Built-in HDD : N
Built-in microphone : Y
Cabling technology : 10/100Base-T(X)
Camera shutter speed : 1/30 [1/25] - 1/15000 s
Camera shutter type : Electronic
Card reader integrated : Y
Compatible memory cards : MicroSDHC, MicroSDXC, SD
Connectivity technology : Wired
Day/night mode : Y
Depth : 158 mm

Effective sensor resolution : 12 pixels
Ethernet interface type : 10 Gigabit Ethernet, Fast Ethernet
Ethernet LAN : Y
Ethernet LAN (RJ-45) ports : 1
Field of view (FOV) angle : 360°
Firmware upgradeable : Y
Fixed focal length : 1.6 mm
Focus adjustment : 2.8
Form factor : Dome
Height : 33 mm
HTTPS encryption : Y
Image quality adjustment : Brightness, Contrast, Saturation
Lens mount interface : Board mount
Lens viewing angle, horizontal : 180°
Lens viewing angle, vertical : 180°
Management software : Web browser; Video Security Client; Video Security App; Bosch Video Management System; Bosch Video Client; or third party software
Maximum memory card size : 2000 GB
Maximum resolution : 3640 x 2160 pixels
Minimum illumination : 0.15 lx
Mounting type : Ceiling/wall
Networking standards : IEEE 802.3af, IEEE 802.3at
Noise reduction : Y
Number of cameras : 1
Operating relative humidity (H-H) : 20 - 93%
Operating temperature (T-T) : -20 - 40 °C
Optical sensor size : 25.4 / 2.3 mm (1 / 2.3»)
Power consumption : 200 mA
Power over Ethernet (PoE) : Y
Power source type : PoE
Privacy masking : Y
Product colour : White
Region of Interest (ROI) encoding : Y
Sensor type : CMOS
Signal-to-Noise Ratio (SNR) : 50 dB
Storage relative humidity (H-H) : 0 - 98%
Storage temperature (T-T) : -20 - 60 °C
Supported audio standards : G.711, 8 kHz sampling rate L16, 16 kHz sampling rate AAC-LC, 48 kbps at 16 kHz sampling rate AAC-LC, 80 kbps at 16 kHz sampling rate
Supported graphics resolutions : 1280 x 720 (HD 720), 1600 x 1200 (UXGA), 1920 x 1080 (HD 1080)
Supported network protocols : IPv4, IPv6, UDP, TCP, HTTP, HTTPS, RTP/RTCP, IGMP V2/V3, ICMP, ICMPv6, RTSP, FTP, ARP, DHCP, APIPA (Auto-IP, link local address), NTP (SNTP), SNMP (V1, V3, MIB-II), 802.1x, DNS, DNSv6, DDNS (DynDNS.org, selfHOST.de, no-ip.com), SMTP, iSCSI, UPnP (SSDP), DiffServ (QoS), LLDP, SOAP, Dropbox, CHAP, digest authentication
Total megapixels : 12 MP
Video compression formats : H.264, M-JPEG
Video motion detection : Y
Video streaming : Y
Weight : 526 g
White balance : Auto
Wide Dynamic Range (WDR) : Y
Width : 158 mm
Wi-Fi : N