

# HANWHA Analog camera HCP-6230H



## DESCRIPTION

### 1080p Analog HD 23x PTZ Dome Camera

- Full HD (1920 x 1080, 30fps) Resolution
- 0.2Lux@F1.6 (Color), 0.01Lux@F1.6 (B/W)
- Powerful 23x Zoom (4.44 ~ 101.2mm), Digital 16x
- Day & Night (ICR), Defog, WDR (120dB), SSNR III
- Preset : 700/sec, Azimuth
- RS-485, Coax Control

## TECHNICAL CHARACTERISTICS

Brand : HANWHA

Part number : HCP-6230H

### Représentation / réalisation :

Type : IP security camera

### Système d'objectif :

Auto focus : Y

AC input voltage : 24 V

Active tampering alarm : Y

Alarm input/output : Y

Back Light Compensation (BLC) : Y

BNC output ports : 1

Camera pan control : Y

Camera shutter speed : 2 - 1/12000 s

Camera shutter type : Electronic

Camera tilt control : Y

Closest focusing distance : 1.4 m

Connectivity technology : Wired

Day/night mode : Y

Depth : 220 mm

Digital zoom : 16x

Flip & mirror : Y
Focal length range : 4.44 - 101.2 mm
Fog proof : Y
Form factor : Dome
Height : 293.6 mm
Highlight Compensation (HLC) : Y
Housing material : Metal, Plastic
IK code : IK10
Image stabilizer : Y
Intelligent Video Surveillance (IVS) system features : Crossing line, Missing object
International Protection (IP) code : IP66
Lens viewing angle, horizontal : 62.8°
Lens viewing angle, vertical : 36.8°
Maximum aperture number : 3.63
Maximum resolution : 1920 x 1080 pixels
Minimum aperture number : 1.6
Minimum illumination : 0.01 lx
Mounting type : Ceiling
Noise reduction : Y
Noise reduction technology : 3D noise reduction
Number of cameras : 1
Number of effective pixels (H x V) : 1944 x 1104 pixels
Number of lenses : 1
Number of sensors : 1
Operating relative humidity (H-H) : 0 - 90%
Operating temperature (T-T) : -50 - 55 °C
Optical sensor size : 25.4 / 2.8 mm (1 / 2.8»)
Optical zoom : 23x
Pan preset speed : 700 °/sec
Pan range : 0 - 360°
Pan speed : 200 °/sec
Placement supported : Indoor & outdoor
Power consumption (max) : 65 W
Power consumption (typical) : 24 W
Power source type : AC
Preset points : Y
Privacy masking : Y
Product colour : Black, Ivory
Progressive scan : Y
PTZ control : Y
Remotely operated : Y
RS-485 ports : 1
Sensor type : CMOS
Signal-to-Noise Ratio (SNR) : 50 dB
Storage relative humidity (H-H) : 0 - 90%
Storage temperature (T-T) : -50 - 60 °C
Tilt angle range : -15 - 195°
Tilt speed : 700 °/sec
Total megapixels : 2 MP
Video motion detection : Y
Weight : 3.3 kg
White balance : ATW, AWC, Indoor, Manual, Mercury lamp, Outdoor, Sodium lamp
Wide Dynamic Range (WDR) : Y

Width : 220 mm

Zoom capability : Y