

EPDU MA 1U (C20 16A 1P)8XC13



DESCRIPTION

Switch and meter outlets & IT equipment across A and B feed: Combines both Switched and Metered Outlet functionality together in 1 ePDU

ePDU G3 Managed models allow complete lights-out control and metering of devices including devices powered across multiple ePDUs. They include IEC Class 1 ($\pm 1\%$) billing grade accuracy, an advanced hot-swap meter with LCD pixel display showing V, W, A and kWh, and the ability to daisy chain 8 ePDUs to share the same network connection and IP address.

TECHNICAL CHARACTERISTICS

Brand : EATON

Part number : EMAH28

Design :

Type : Single-phase

Caractéristiques :

Certification : CB, CE, EN 60950-1:2006/A11:2009/A12:2010/A12:2011\ nEN 61000-6-2:2005\ nEN 50581 : 2012, REACH, WEEE\ nISO 9001:2008 / ISO 14001:2004

AC input frequency : 50 Hz

AC outlet types : C13 coupler

AC outlets quantity : 8 AC outlet(s)

Cable colour : Black

Cable length : 3 m

Cables included : LAN (RJ-45)

Depth : 203 mm

Dimensions (WxDxH) : 445 x 203 x 43 mm

Display : LCD

Ethernet LAN (RJ-45) ports : 1

Firmware upgradeable : Y

Firmware upgradeable via : Network, USB

Form factor : Rackmount

Height : 43 mm

LED indicators : Y

Management protocols : SNMP, Telnet
Maximum current : 16 A
Maximum input current per phase : 16 A
Maximum power : 3700 W
Mounting : Horizontal
Nominal input voltage : 230 V
Nominal output voltage : 230 V
Operating temperature (T-T) : 0 - 60 °C
Output connections : 8 x C13
Package depth : 570 mm
Package height : 195 mm
Package weight : 5.8 kg
Package width : 375 mm
PDU types : Managed
Power plug : C20 coupler
Product colour : Black
Rack capacity : 1U
Rack mount kit : Y
Rack mounting : Y
Serial ports quantity : 1
Supported network protocols : HTTP, HTTPS, SSL, FTP, SMTP, DNS, DHCP, LDAP, RADIUS
Sustainability certificates : RoHS
Weight : 3.4 kg
Width : 445 mm