

PHILIPS- Signage screen 55" 55BDL3650QE/00



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : PHILIPS
Part number : 55BDL3650QE/00
Représentation / réalisation :
Open Pluggable Specification (OPS) : Yes
Détails techniques :
Compliance certificates : BSMI, CB, CE, ETL, Federal Communications Commission (FCC), RoHS, VCCI
AC input frequency : 50 - 60 Hz
AC input voltage : 100 - 240 V
Audio formats supported : AAC, HE-AAC, MPEG
Bezel width (bottom) : 1.39 cm
Bezel width (side) : 1.39 cm
Bezel width (top) : 1.39 cm
Built-in processor : Yes
Built-in speaker(s) : Yes
Cables included : AC, RS-232
Card reader integrated : Yes
Compatible memory cards : MicroSD (TransFlash)
Computer system : No
Contrast ratio (dynamic) : 500000:1
Contrast ratio (typical) : 1200:1
Display brightness : 350 cd/m²
Display depth : 63.6 mm
Display diagonal : 138.7 cm (54.6»)
Display diagonal (metric) : 125.7 cm
Display height : 712.6 mm
Display number of colours : 1.06 billion colours
Display resolution : 3840 x 2160 pixels

Display weight : 17.2 kg
Display width : 1241.8 mm
DVI port : Yes
DVI-I ports quantity : 1
Energy efficiency class (SDR) : D
Ethernet LAN : Yes
Ethernet LAN (RJ-45) ports : 1
HD type : 4K Ultra HD
HDMI ports quantity : 2
HDMI version : 2.0
Image formats supported : BMP, JPEG, PNG
Infrared data port : Yes
Internal memory : 3000 MB
LED backlight : Yes
LED backlighting type : Direct-LED
Mean time between failures (MTBF) : 30000 h
Native aspect ratio : 16:9
Number of built-in speakers : 2
On Screen Display (OSD) : Yes
On Screen Display (OSD) languages : Arabic, Simplified Chinese, Traditional Chinese, German, English, Spanish, French, Italian, Japanese, Polish, Russian, Turkish
Operating relative humidity (H-H) : 20 - 80%
Operating system installed : Android 10
Operating temperature (T-T) : 0 - 40 °C
Orientation : Horizontal/Vertical
Panel mounting interface : 400 x 400 mm
Panel type : IPS
Pixel pitch : 0.2854 x 0.2854 mm
Placement supported : Indoor
Power consumption (max) : 120 W
Power consumption (standby) : 0.5 W
Power consumption (typical) : 70 W
Product colour : Black
Product design : Digital signage flat panel
Purpose : Universal
Response time : 8 ms
RMS rated power : 20 W
RS-232 interface : Yes
Screen shape : Flat
Storage relative humidity (H-H) : 5 - 95%
Storage temperature (T-T) : -20 - 60 °C
Tiled bezel width : 1.5 cm
Touchscreen : No
USB 2:0 Type-B ports quantity : 2
USB 3:2 Gen 1 (3:1 Gen 1) Type-A ports quantity : 2
USB port : Yes
USB ports quantity : 4
USB version : 2.0
VESA mounting : Yes
Video formats supported : H.263, H.264, H.265, MPEG1, MPEG2, VP8, VP9
Viewing angle, horizontal : 178°
Viewing angle, vertical : 178°
Warranty period : 3 year(s)
Wi-Fi : Yes