

93PS-15(20)-15-1x9Ah-LL-6



DESCRIPTION

The 93PS range includes several features that are unique to Eaton and designed to provide the highest possible availability for critical infrastructure. These include: Hot Sync, Eaton's patented technology for load sharing between UPSs, which eliminates any single point of failure in a parallel operating UPS system; and Advanced Battery Management (ABM), which enables intelligent charging and extends the lifetime of the batteries. The Eaton 93PS also includes features to ensure safe installation and use, thanks to pre-designed, pre-tested and pre-installed integrated safety components, such as the backfeed protection and ultra-rapid fuses in the static switch.

The new models also support Eaton's Intelligent Power Management (IPM) software, which is an ideal fit for smaller data centers especially because of its ability to integrate with existing systems and to automate power management functions. Eaton's IPM enables a data center or IT manager to monitor and manage the UPS as an integral part of the power and IT infrastructure, through a single pane of glass. The web-based interface allows monitoring of multiple UPSs and other power equipment. In virtualized data centers, the IPM can be linked to existing virtualization management systems, and allows users to easily configure policy-based automation for power events, such as load shedding or controlled shut down.

TECHNICAL CHARACTERISTICS

Brand : EATON

Part number : BA51A5206A01100000

Design :

Certification : IEC 62040-1 IEC 62040-2 IEC 62040-3

Battery capacity : 9 Ah

Battery life (max) : 10 year(s)

Battery technology : Sealed Lead Acid (VRLA)

Battery voltage : 12 V

Depth : 750 mm

Efficiency : 99%

Form factor : Tower

Height : 1300 mm

Input current Total Harmonic Distortion (THD) : 3%

Input frequency : 50/60 Hz

Input operation voltage (max) : 415 V

Input operation voltage (min) : 220 V
Input power factor : 0.99
International Protection (IP) code : IP20
LED indicators : Y
Noise level : 60 dB
Number of battery cells : 192
Number of input phases : 3
Number of output phases : 3
Operating relative humidity (H-H) : 5 - 95%
Operating temperature (T-T) : 0 - 40 °C
Output operation voltage (max) : 415 V
Output operation voltage (min) : 220 V
Output power : 15000 W
Output power capacity : 15 kVA
Output power factor : 1
Output voltage Total Harmonic Distortion (THD) : 1%
Power factor : 1
Product colour : Black
Serial interface : Y
Serial interface type : RS-232
Serial ports quantity : 1
Storage relative humidity (H-H) : 5 - 95%
Storage temperature (T-T) : -25 - 55 °C
UPS topology : Double-conversion (Online)
USB port : Y
Waveform : Sine
Width : 335 mm