



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : TP-LINK
Part number : CPE710
Caractéristiques :
5 GHz : Yes
Caractéristiques de gestion :
Syslog : Yes
Design :
Certification : CE, FCC, RoHS, IC
2:4 GHz : No
AC input frequency : 50 - 60 Hz
AC input voltage : 100 - 240 V
Antenna gain level (max) : 23 dBi
Auto Wireless Distribution System (WDS) : Yes
Automatic channel selection : Yes
Built-in processor : Yes
Cables included : AC
Channel bandwidth : 80 MHz
Compatible operating systems : Microsoft Windows 98SE, NT, 2000, XP, Vista, Windows 10, Windows 8, Windows 7, MAC OS, NetWare, UNIX, Linux
Depth : 280 mm
Dynamic Frequency Selection (DFS) : Yes
Ethernet LAN (RJ-45) ports : 1
Ethernet LAN data rates : 10,100,1000 Mbit/s
Flash memory : 16 MB
Frequency band : 5.15 - 5.85 GHz
Harmonized System (HS) code : 85176990
Height : 207 mm
Housing material : Plastic

IGMP snooping : Yes
Internal memory : 128 MB
International Protection (IP) code : IP65
LED indicators : Power
MAC address filtering : Yes
Maximum data transfer rate : 867 Mbit/s
MIMO : Yes
Networking standards : IEEE 802.11a, IEEE 802.11ac, IEEE 802.11n
Operating relative humidity (H-H) : 10 - 90%
Operating temperature (T-T) : -40 - 70 °C
Output current : 0.6 A
Output voltage : 24 V
Package type : Box
Placement : Pole
PoE adapter included : Yes
Power over Ethernet (PoE) : Yes
Processor frequency : 750 MHz
Product colour : White
Quick start guide : Yes
Reset button : Yes
Security algorithms : HTTPS, SNMP, SSH, WPA, WPA2, WPA2-AES, WPA2-PSK, WPA2-TKIP
Service Set Identifier (SSID) features : Multiple SSIDs, SSID broadcast, SSID broadcast on/off
Storage relative humidity (H-H) : 5 - 95%
Storage temperature (T-T) : -40 - 70 °C
Transmitting power : 27 dBmW
Universal Plug and Play (UPnP) : Yes
Web-based management : Yes
Width : 366 mm
Wireless isolation : Yes