

HANWHA IP camera TNO-4030T



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : HANWHA

Part number : TNO-4030T

Représentation / réalisation :

Type : IP security camera

Réseau :

Bluetooth : N

Connectivité :

Interface : RJ-45

AC input voltage : 24 V

Alarm input/output : Y

Audio formats supported : ADPCM

Audio system : 2-way

Built-in HDD : N

Cabling technology : 10/100Base-T(X)

Camera pan control : N

Camera tilt control : N

Card reader integrated : Y

Closest focusing distance : 5 m

Compatible memory cards : SD, SDHC, SDXC

Composite video out : 1

Connectivity technology : Wired

DC output voltage : 12

Diameter : 10.2 cm

Ethernet interface type : Fast Ethernet

Ethernet LAN : Y

Ethernet LAN (RJ-45) ports : 1

Fixed focal length : 1.3 cm

Fixed focus : Y
Flip & mirror : Y
Form factor : Bullet
Frame rate : 30 fps
Housing material : Aluminium
IK code : IK10
Image stabilizer : Y
International Protection (IP) code : IP66
IP address filtering : Y
Length : 401.8 mm
Lens viewing angle, diagonal : 61.6°
Lens viewing angle, horizontal : 48.6°
Lens viewing angle, vertical : 36.4°
Mac compatibility : Y
Mac operating systems supported : Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra
Maximum aperture number : 1
Maximum memory card size : 256 GB
Maximum resolution : 640 x 480 pixels
Microphone in : Y
Mirror : Y
Mounting type : Ceiling/wall
Networking standards : IEEE 802.1x, IEEE 802.3af
Number of cameras : 1
Number of lenses : 1
Number of users : 20 user(s)
Operating relative humidity (H-H) : 0 - 90%
Operating temperature (T-T) : -40 - 60 °C
Placement supported : Indoor & outdoor
Power consumption (max) : 10.5 W
Power consumption (Power over Ethernet (PoE)) : 10 W
Power source type : AC, DC, PoE
Privacy masking : Y
Product colour : White
Protection features : Vandal proof
Quality of Service (QoS) support : Y
Security algorithms : EAP-TLS, HTTPS, LEAP, SSL/TLS
Storage relative humidity (H-H) : 0 - 90%
Storage temperature (T-T) : -50 - 60 °C
Streaming method : Multicast, Unicast
Supported graphics resolutions : 320 x 240, 640 x 360, 640 x 480 (VGA)
Supported network protocols : TCP/IP, UDP/IP, RTP (UDP), RTP (TCP), RTCP,RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, PPPoE, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3 (MIB-2), ARP, DNS, DDNS, QoS, UPnP, Bonjour
USB port : Y
Video compression formats : H.264, H.265, M-JPEG, MPEG4
Video motion detection : Y
Video streaming : Y
Voice codecs : G.711, G.711ulaw, G.726
Web-based management : Y
Weight : 3.12 kg
Wi-Fi : N
Windows operating systems supported : Windows 10, Windows 7, Windows 8.1