

HANWHA- Camera XNP-C6403RW



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : HANWHA
Part number : XNP-C6403RW
Représentation / réalisation :
Type : IP security camera
Active tampering alarm : Yes
Angle of rotation : 360°
Audio detection : Yes
Auto-tracking : Yes
Back Light Compensation (BLC) : Yes
Bit rate control : Constant Bit Rate (CBR), Variable Bit Rate (VBR)
Built-in HDD : No
Camera shutter speed : 2- 1/12000 s
Card reader integrated : Yes
Closest focusing distance : 3 m
Cloud-managed : Yes
Compatible memory cards : MicroSD (TransFlash), MicroSDHC, MicroSDXC
Connectivity technology : Wired
Day/night mode : Yes
Detect distance (tele) : 2340.4 m
Detect distance (wide) : 59.5 m
Diameter : 18.5 cm
Digital zoom : 32x
Dynamic range : 150 dB
Ethernet LAN : Yes
Ethernet LAN (RJ-45) ports : 1
Flash memory : 512 MB
Flip & mirror : Yes

Focal length range : 4.25 - 170 mm
Fog proof : Yes
Form factor : Dome
Frame rate : 60 fps
Height : 318.8 mm
Highlight Compensation (HLC) : Yes
Housing material : Aluminium, Polycarbonate (PC)
Identify distance (tele) : 234 m
Identify distance (wide) : 6 m
IK code : IK10
Infra-red wavelength : 850 nm
Intelligent Video Surveillance (IVS) system features : Human detection, Vehicle detection, Face detection, Region entrance detection, Region exiting detection, Intrusion, Line crossing detection, Defocus
International Protection (IP) code : IP66
LED type : IR
Lens viewing angle, horizontal : 65.66°
Lens viewing angle, vertical : 39.4°
Maximum memory card size : 1 TB
Maximum resolution : 1920 x 1080 pixels
Minimum illumination : 0.005 lx
Mounting type : Ceiling/wall
Night vision : Yes
Night vision distance : 200 m
Noise reduction : Yes
Number of cameras : 1
Number of lenses : 1
Number of users : 20 user(s)
Observe distance (tele) : 936.2 m
Observe distance (wide) : 23.8 m
Operating relative humidity (H-H) : 0 - 100%
Operating temperature (T-T) : -40 - 55 °C
Optical sensor size : 25.4 / 2.8 mm (1 / 2.8»)
Optical zoom : 40x
Pan manual speed : 0.024 - 250 °/sec
Pan preset speed : 500 °/sec
Placement supported : Outdoor
Power consumption (Power over Ethernet (PoE)) : 26 W
Power source type : PoE
Privacy protection : Yes
Product colour : White, Black
PTZ control : Yes
Quality of Service (QoS) support : Yes
RAM capacity : 4000 MB
Recognize distance (tele) : 468.1 m
Recognize distance (wide) : 11.9 m
Security algorithms : HTTPS, SRTP, EAP-TLS, EAP-LEAP, EAP-PEAP, MSCHAPv2, 802.1x RADIUS
Sensor type : CMOS
Storage relative humidity (H-H) : 0 - 90%
Storage temperature (T-T) : -50 - 60 °C
Streaming method : Unicast, Multicast
Supported graphics resolutions : 320 x 240, 640 x 360, 640 x 480 (VGA), 720 x 480, 720 x 576, 800 x 448, 800 x 600 (SVGA), 1024 x 768 (XGA), 1280 x 960, 1280 x 720 (HD 720), 1280 x 1024 (SXGA), 1920 x 1080 (HD 1080)
Supported network protocols : IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SFTP, SMTP, ICMP, IGMP,

SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, UPnP, Bonjour, LLDP, CDP, SRTP(TCP, UDP Unicast), MQTT, NTCIP 1205
Tilt angle range : -20 - 90°
Tilt manual speed : 0.024 - 250 °/sec
Tilt preset speed : 350 °/sec
Total megapixels : 2 MP
Video compression formats : H.264, H.265
Video intelligence analytic : Yes
Video motion detection : Yes
Weight : 5.6 kg
White balance : ATW, AWC, Manual, Outdoor, Mercury lamp, Sodium lamp, Indoor
Wide Dynamic Range (WDR) : Yes
Wiper included : Yes
Zoom capability : Yes