

EPDU IL 0U (309 32A 3P)1X309



DESCRIPTION

New ePDU G3 In-Line Metered Input models upgrade existing basic installation to include, including $\pm 1\%$ billing grade accuracy, an advanced LCD pixel display, a hot-swap meter and the ability to daisy chain four ePDUs to share the same network connection and IP address.

TECHNICAL CHARACTERISTICS

Brand : EATON

Part number : EILB15

Design :

Type : Three-phase

AC input frequency : 50 Hz

AC outlet types : IEC 60309

AC outlets quantity : 1 AC outlet(s)

Cable colour : Black

Cable length : 3 m

Cables included : LAN (RJ-45)

Depth : 443 mm

Dimensions (WxDxH) : 52 x 443 x 53 mm

Display : LCD

Ethernet LAN (RJ-45) ports : 1

Firmware upgradeable : Y

Firmware upgradeable via : Network, USB

Form factor : Rackmount

Height : 53 mm

LED indicators : Y

Management protocols : SNMP, Telnet

Maximum current : 32 A

Maximum input current per phase : 32 A

Maximum power : 22000 W

Mounting : Vertical

Nominal input voltage : 400 V

Nominal output voltage : 230 V

Operating temperature (T-T) : 0 - 60 °C

Output connections : 1 x IEC 309

Package weight : 6 kg

PDU types : Metered

Power plug : IEC 60309

Product colour : Black

Rack capacity : 0U

Rack mount kit : Y

Rack mounting : Y

Sustainability certificates : RoHS

Weight : 4.98 kg

Width : 52 mm