

Eaton 9PX 11000i 3:1 HotSwap



DESCRIPTION

The Eaton 9PX UPS provides energy-efficient power protection for small & medium Datacentres, IT rooms and Infrastructure. Delivering double conversion protection with 40% less energy usage and 28% more power 9PX is the perfect UPS for IT and Facility managers that are concerned by energy cost and are looking for next generation power protection solutions.

TECHNICAL CHARACTERISTICS

Brand : EATON

Part number : 9PX11KIBP31

Design :

Certification : IEC/EN 62040-1, IEC/EN 62040 -2, IEC/EN 62040-3 (Performance), CE, CB report (TUV)

AC outlet types : C19 coupler, Terminal

AC outlets quantity : 5 AC outlet(s)

Automatic battery test : Y

Battery technology : Sealed Lead Acid (VRLA)

Built-in fan : Y

Bundled software : Intelligent Power Software suite

Cooling type : Active

Depth : 700 mm

Display type : LCD

Efficiency : 0.95%

Form factor : Rackmount/Tower

Harmonized System (HS) code : 85078000

Height : 260 mm

Hot-swap battery : Y

Input current Total Harmonic Distortion (THD) : 5%

Input frequency : 40/70 Hz

Input operation voltage (max) : 480 V

Input operation voltage (min) : 305 V

LED indicators : Y

Management card included : N

Noise level : 50 dB

Nominal input voltage : 400 V
Nominal output voltage : 230 V
Number of input phases : 3
Operating temperature (T-T) : 0 - 40 °C
Output frequency : 50/60 Hz
Output operation voltage (max) : 240 V
Output operation voltage (min) : 200 V
Output power : 10000 W
Output power capacity : 11 kVA
Output voltage Total Harmonic Distortion (THD) : 2%
Power factor : 0.9
Power plug : Terminal
Product colour : Black
Rack capacity : 6U
RS-232 ports : 1
Safety : IEC/EN 62040-1
Serial ports quantity : 1
Sustainability certificates : ENERGY STAR
Typical backup time at half load : 13 min
UPS topology : Double-conversion (Online)
USB 2:0 ports quantity : 1
USB port : Y
Waveform : Pure sine
Weight : 88 kg
Width : 440 mm