

Eaton 9PX 2200i RT3U



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : EATON
Part number : 9PX2200IRT3U
Design :
Certification : IEC/EN 62040-1, UL 1778, CSA 22.2, IEC/EN 62040 -2, FCC Class B, CISPR22 Class B, CE /CB report (TUV) / cULus / EAC /RCM / KC / Energy Star
AC outlet types : C13 coupler, C19 coupler
AC outlets quantity : 10 AC outlet(s)
Automatic battery test : Y
Battery technology : Sealed Lead Acid (VRLA)
Bundled software : Intelligent Power Software suite
Depth : 485 mm
Display type : LCD
Efficiency : 93.5%
Form factor : Rackmount/Tower
Harmonized System (HS) code : 85078000
Height : 130 mm
Hot-swap battery : Y
Input frequency : 40/70 Hz
Input operation voltage (max) : 276 V
Input operation voltage (min) : 176 V
LED indicators : Y
Management card included : N
Noise level : 40 dB
Nominal input voltage : 230 V
Nominal output voltage : 230 V
Number of input phases : 1
Operating temperature (T-T) : 0 - 40 °C
Output frequency : 50/60 Hz

Output operation voltage (max) : 240 V
Output operation voltage (min) : 200 V
Output power : 2200 W
Output power capacity : 2.2 kVA
Power factor : 1
Power plug : C20 coupler
Product colour : Black
Rack capacity : 3U
Rack mount kit : Y
RS-232 ports : 1
Safety : IEC/EN 62040-1, UL 1778, CSA 22.2
Sustainability certificates : ENERGY STAR
Typical backup time at half load : 10 min
UPS topology : Double-conversion (Online)
USB 2:0 ports quantity : 1
USB port : Y
Waveform : Pure sine
Weight : 24.5 kg
Width : 440 mm