

Tp-link Archer C6 Router WiFi 5 AC1200 Gigabit MU-MIMO



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : TP-LINK

Part number : ARCHER C6

Sécurité :

Stateful Packet Inspection (SPI) : Y

Réseaux mobiles :

3G : N

4G : N

Connexion WAN :

Ethernet WAN : Y

DSL WAN : N

3G/4G USB modem compatibility : N

AC adapter included : Y

Antenna design : External

Antennas quantity : 5

Cables included : LAN (RJ-45)

Cabling technology : 10/100Base-T(X)

DC-in jack : Y

Depth : 144 mm

DHCP client : Y

DHCP server : Y

DMZ support : Y

DoS attack prevention : Y

Ethernet LAN : Y

Ethernet LAN (RJ-45) ports : 5

Ethernet LAN data rates : 10,100 Mbit/s

Ethernet LAN interface type : Fast Ethernet

Filtering : Y

Firewall : Y
Guest access : Y
Harmonized System (HS) code : 85176990
Height : 37 mm
Indication light : Y
IP address filtering : Y
LED indicators : LAN, Power, WLAN
Linux operating systems supported : Y
MAC address filtering : Y
Mac compatibility : Y
Mac operating systems supported : macOS
Manual : Y
Maximum data transfer rate : 1 Mbit/s
Memory card slot(s) : N
Mobile network generation : 4G
Networking standards : IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
On/off switch : Y
Operating relative humidity (H-H) : 10 - 90%
Operating temperature (T-T) : 0 - 40 °C
Output current : 1 A
Output voltage : 12 V
Package type : Box
Port forwarding : Y
Power source type : AC
Product colour : White
Product type : Tabletop router
Quick installation guide : Y
Quick start guide : Y
Receiver sensitivity : 5GHz: 11a 54M: -76dBm 11ac VHT20 MCS8: -70dBm 11ac VHT40 MCS9: -65.5dBm 11ac VHT80 MCS9: -61.5dBm 2.4G: 11g 54M: -76dBm 11n HT20 MCS7: -74dBm 11n HT40 MCS7: -71dBm
Reset button : Y
Security algorithms : 64-bit WEP, 128-bit WEP, WPA, WPA-PSK, WPA2, WPA2-PSK
SIM card slot : N
Storage relative humidity (H-H) : 5 - 90%
Storage temperature (T-T) : -40 - 70 °C
Top Wi-Fi standard : Wi-Fi 5 (802.11ac)
Transmit power : CE: <20dBm(2.4GHz), <23dBm(5GHz)
Universal Plug and Play (UPnP) : Y
USB port : N
VoIP protocols : IPv4, IPv6
VPN Passthrough : Y
VPN support : PPTP, L2TP, IPSec
WAN connection type : RJ-45
Width : 230 mm
Wi-Fi band : Dual-band (2.4 GHz / 5 GHz)
Wi-Fi standards : 802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac)
Windows operating systems supported : Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 Pro, Windows 10 Pro x64, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64

nal, Windows XP Professional x64

WLAN data transfer rate (first band) : 450 Mbit/s

WLAN data transfer rate (max) : 867 Mbit/s

WLAN data transfer rate (second band) : 867 Mbit/s

WPS push button : Y