

# HANWHA- Camera XNO-6123R



## DESCRIPTION

## TECHNICAL CHARACTERISTICS

Brand : HANWHA

Part number : XNO-6123R

### Représentation / réalisation :

Type : IP security camera

### Réseau :

Bluetooth : No

### Système d'objectif :

Auto focus : Yes

### Détails techniques :

Iris : Yes

Certification : IP66/67, IK10, NEMA4X, NEMA-TS 2(2.2.8, 2.2.9)

Alarm input/output : Yes

Alert notification type : E-mail

Angle of rotation : 270°

Antenna type : Internal

Audio formats supported : AAC-LC, ADPCM, G.711 -law, G.726

Audio output : Line out

Back Light Compensation (BLC) : Yes

Bit rate control : Constant Bit Rate (CBR), Variable Bit Rate (VBR)

Built-in HDD : No

Camera shutter speed : 2 - 1/12.000 s

Card reader integrated : Yes

Compatible memory cards : SD, SDHC, SDXC

Compliance certificates : CE, EAC, Federal Communications Commission (FCC), ICES, RCM, UKCA, UL, VCCI

Connectivity technology : Wired

Day/night mode : Yes

DC output current : 0.05 A

DC output voltage : 12
Detect distance (tele) : 879.5 m
Detect distance (wide) : 73.8 m
Diameter : 9.34 cm
Digest authentication : Yes
Digital zoom : 32x
Dynamic range : 150 dB
Ethernet interface type : Gigabit Ethernet
Ethernet LAN : Yes
Ethernet LAN (RJ-45) ports : 1
Flash memory : 512 MB
Flip & mirror : Yes
Focal length range : 5.2 - 62.4 mm
Form factor : Bullet
Frame rate : 120 fps
Gain control type : Manual
Highlight Compensation (HLC) : Yes
Horizontal field of view (optical module) : 55°
Housing material : Aluminium
HTTPS encryption : Yes
Identify distance (tele) : 88 m
Identify distance (wide) : 7.4 m
IK code : IK10
Image stabilizer : Yes
International Protection (IP) code : IP66, IP67
IP address filtering : Yes
Languages support : Simplified Chinese, Czech, German, Dutch, English, Spanish, French, Greek, Hungarian, Italian, Japanese, Korean, Polish, Turkish
LED type : IR
Length : 298.4 mm
Maximum aperture number : 3
Maximum resolution : 1920 x 1080 pixels
Memory card included : SD
Microphone in : Yes
Minimum illumination : 0.03 lx
Mounting type : Ceiling/Wall/Pole
Network access storage (NAS) : Yes
Night vision : Yes
Night vision distance : 90 m
Noise reduction technology : Smart Super Noise Reduction V (SSNR V), WiseNR
Number of cameras : 1
Number of lenses : 1
Observe distance (tele) : 351.8 m
Observe distance (wide) : 29.5 m
Operating relative humidity (H-H) : 0 - 95%
Operating temperature (T-T) : -40 - 60 °C
Optical sensor size : 25.4 / 2.8 mm (1 / 2.8»)
Optical zoom : 12x
Placement supported : Outdoor
Power consumption (max) : 16.5 W
Power consumption (Power over Ethernet (PoE)) : 15.5 W
Power consumption (typical) : 13.1 W
Power over Ethernet (PoE) : Yes
Power source type : DC, PoE

Privacy masking : Yes
Product colour : White
PTZ control : Yes
RAM capacity : 2000 MB
Recognize distance (tele) : 175.9 m
Recognize distance (wide) : 14.8 m
Sample rate : 16000 kHz
Security algorithms : 802.1x RADIUS, EAP-LEAP, EAP-PEAP, EAP-TLS, FIPS 140-2, HTTPS, MSCHAPv2
Sensor type : CMOS
Storage relative humidity (H-H) : 0 - 95%
Storage temperature (T-T) : -50 - 60 °C
Streaming method : Multicast, Unicast
Supported graphics resolutions : 320 x 240, 640 x 360, 640 x 480 (VGA), 720 x 480, 720 x 576, 800 x 448, 800 x 600 (SVGA), 1024 x 768 (XGA), 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1280 x 960, 1600 x 1200, 1920 x 1080 (HD 1080)
Supported network protocols : IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP,RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, UPnP, Bonjour, LLDP, CDP, SRTP(TCP, UDP Unicast), MQTT
Technical features : LDC support
&e