



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : EATON	
Part number : 9E1000IR	
Design :	
Certification :	IEC/EN 62040-1 IEC/EN 62040-2 CE
AC outlet types :	C13 coupler, C14 coupler
AC outlets quantity :	4 AC outlet(s)
Audible alarm(s) :	Yes
Battery capacity :	7 Ah
Battery technology :	Lead-Acid
Battery voltage :	12 V
Cables included :	Output power cable, USB cable
Control type :	Buttons
Depth :	438 mm
Display type :	LCD
Efficiency :	90%
Efficiency (ECO mode) :	95.5%
Form factor :	Tower
Heat dissipation :	375 BTU/h
Height :	86.5 mm
Input frequency :	40/70 Hz
Input operation voltage (max) :	276 V
Input operation voltage (min) :	120 V
Input power factor :	99
LED indicators :	Yes
Noise level :	41 dB
Number of batteries supported :	3
Number of input phases :	1

Number of output phases : 1
Operating relative humidity (H-H) : 0 - 96%
Operating temperature (T-T) : 0 - 40 °C
Output frequency : 50/60 Hz
Output operation voltage (max) : 240 V
Output operation voltage (min) : 220 V
Output power : 900 W
Output power capacity : 1 kVA
Output power factor : 0.9
Power plug : C13 coupler
Power source type : AC
Product colour : Black
Quick installation guide : Yes
Rack capacity : 2U
Rack mount kit : Yes
RS-232 ports : 1
Serial interface : Yes
Serial interface type : RS-232
Serial ports quantity : 1
Sustainability certificates : CE
Sustainability compliance : Yes
Typical backup time at full load : 6 min
Typical backup time at half load : 15 min
UPS topology : Double-conversion (Online)
USB port : Yes
Waveform : Sine
Weight : 17.6 kg
Width : 438 mm