



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : OPTICON
Part number : 14164
Numérisation :
Type : Handheld bar code reader
Représentation / réalisation :
Certification : CE, FCC, VCCI, JIS-C-6802 2, IEC60825-1 2, FDA CDRH, II, EN55032, EN61000 B
2D (matrix & stacked) barcodes supported : Not supported
Buzzer : Yes
Cable length : 2 m
Compliance certificates : RoHS
Connectivity technology : Wired
Depth : 31.5 mm
Harmonized System (HS) code : 84716070
Height : 161.1 mm
Housing material : Acrylonitrile butadiene styrene (ABS)
Input voltage : 5 V
International Protection (IP) code : IP42
Keys quantity : 1 keys
LED indicators : Yes
Linear (1D) barcodes supported : Codabar, Code 11, Code 128, Code 39, Code 93, GS1-128 (UCC/EAN-128), Interleaved 2 of 5, JAN, MSI, Plessey, Telepen, Trioptic, U.P.C.
Operating relative humidity (H-H) : 5 - 90%
Operating temperature (T-T) : -5 - 50 °C
Pitch reading angle : -35 - 35°
Power consumption : 135 mA
Power source type : USB
Product colour : Black

Read rate (max) : 100 reads/s
Scanner type : 1D
Standard interfaces : USB
Storage temperature (T-T) : -30 - 60 °C
Tilt reading angle : -20 - 20°
USB version : 2.0
Wavelength : 650 nm
Weight : 75 g
Width : 56.3 mm
Yaw reading angle : -50 - 50°