

Eaton 9PX 6000i 3:1 RT6U HotSwap Netpack



DESCRIPTION

The Eaton 9PX UPS provides energy-efficient power protection for small & medium Datacentres, IT rooms and Infrastructure. Delivering double conversion protection with 40% less energy usage and 28% more power 9PX is the perfect UPS for IT and Facility managers that are concerned by energy cost and are looking for next generation power protection solutions.

TECHNICAL CHARACTERISTICS

Brand : EATON
Part number : 9PX6KIRTNBP31
Design :
Certification : IEC/EN 62040-1, IEC/EN 62040 -2, IEC/EN 62040-3 (Performance), CE, CB report (TUV)
AC outlet types : C19 coupler, Terminal
AC outlets quantity : 5 AC outlet(s)
Automatic battery test : Y
Battery technology : Sealed Lead Acid (VRLA)
Built-in fan : Y
Bundled software : Intelligent Power Software suite
Cooling type : Active
Depth : 700 mm
Display type : LCD
Efficiency : 94%
Form factor : Rackmount/Tower
Harmonized System (HS) code : 85078000
Height : 260 mm
Hot-swap battery : Y
Input current Total Harmonic Distortion (THD) : 5%
Input frequency : 40/70 Hz
Input operation voltage (max) : 480 V
Input operation voltage (min) : 305 V
LED indicators : Y
Management card included : Y
Noise level : 48 dB

Nominal input voltage : 400 V
Nominal output voltage : 230 V
Number of input phases : 3
Operating temperature (T-T) : 0 - 40 °C
Output frequency : 50/60 Hz
Output operation voltage (max) : 240 V
Output operation voltage (min) : 200 V
Output power : 5400 W
Output power capacity : 6 kVA
Output voltage Total Harmonic Distortion (THD) : 2%
Power factor : 0.9
Power plug : Terminal
Product colour : Black
Rack capacity : 6U
Rack mount kit : Y
RS-232 ports : 1
Safety : IEC/EN 62040-1
Serial ports quantity : 1
Sustainability certificates : ENERGY STAR
Typical backup time at half load : 30 min
UPS topology : Double-conversion (Online)
USB 2:0 ports quantity : 1
USB port : Y
Waveform : Pure sine
Weight : 88 kg
Width : 440 mm