

HANWHA- Camera PNM-C12083RVD



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand :	HANWHA
Part number :	PNM-C12083RVD
Représentation / réalisation :	
Type :	IP security camera
Angle of rotation :	180°
Back Light Compensation (BLC) :	Yes
Camera shutter speed :	1/5 ~ 1/12,000 s
Camera shutter type :	Electronic
Connectivity technology :	Wired
Depth :	135 mm
Detect distance :	1.5 m
Detect distance (tele) :	153.1 m
Detect distance (wide) :	59.9 m
Dynamic range :	120 dB
Flash memory :	512 MB
Focal length range :	3.54 - 6.69 mm
Form factor :	Dome
Frame rate :	15 fps
Gain control type :	Manual
Height :	93.2 mm
Horizontal field of view (thermal module) :	96 - 47°
Housing material :	Aluminium
HTTPS encryption :	Yes
Identify distance (tele) :	15.3 m
Identify distance (wide) :	6 m
Internal memory :	4 MB
Maximum aperture number :	2.64

Maximum memory card size : 512 GB
Maximum resolution : 3328 x 1872 pixels
Minimum illumination : 0.016 lx
Motion sensor : Yes
Mounting type : Ceiling
Night vision : Yes
Number of cameras : 1
Number of Privacy masking areas : 6
Number of users : 10 user(s)
Observe distance (tele) : 61.2 m
Observe distance (wide) : 24 m
Operating relative humidity (H-H) : 0 - 95%
Operating temperature (T-T) : -40 - 55 °C
Optical sensor size : 25.4 / 2.8 mm (1 / 2.8»)
Optical zoom : 1.9x
Pan range : 0 - 355°
Placement supported : Outdoor
Product colour : White
Recognize distance (tele) : 30.6 m
Recognize distance (wide) : 12 m
Sensor type : CMOS
Storage relative humidity (H-H) : 0 - 95%
Storage temperature (T-T) : -50 - 60 °C
Supported graphics resolutions : 2688 x 1520, 2592 x 1944, 3072 x 1728, 1920 x 1080 (HD 1080), 1600 x 1200, 1280 x 1024 (SXGA), 1280 x 960, 1280 x 720 (HD 720), 1024 x 768 (XGA), 800 x 600 (SVGA), 800 x 448, 720 x 576, 720 x 480, 640 x 480 (VGA), 640 x 360, 320 x 240
Supported network protocols : IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, UPnP, Bonjour, LLDP, SRTP(TCP, UDP Unicast)
Tilt angle range : 0 - 78°
Total megapixels : 6 MP
USB port : Yes
Vertical field of view (thermal module) : 51°
Weight : 1.33 kg
White balance : ATW, AWC, Manual, Indoor, Outdoor
Width : 215 mm
Wi-Fi : Yes