

Eaton FLEXPDU 8 FR 1U



DESCRIPTION

Power distribution

The no hassle solution for improving availability and adding flexibility for single phase UPSs.

Eaton FlexPDU

Having the right connectors just where you need them

- FlexPDUs (Power Distribution Units) are flexible mounting multiway socket blocks for easy connection of multiple loads either as free-standing or on rack-mounted UPSs
- FlexPDUs have a large number of sockets (8 French sockets, 6 BS sockets or 12 IEC 10 A sockets) which fit into a very compact unit (1U - 19)
- FlexPDUs are easy to implement into any type of installation: they can be rack mounted horizontally (1U) or vertically or directly onto all Eaton RT format (rack/tower) UPSs Eaton HotSwap MBP
- High availability for all UPSs up to 11 kVA.
- HotSwap MBP provides a maintenance bypass for all UPSs. UPSs can be hot swapped or upgraded without interrupting the power supply.
- HotSwap MBP are available with multiple power ratings:
3000 VA, 6000 VA, 11000 VA, 11000 VA (3 ph Input).
- HotSwap MBP provides compatibility with any UPS now and in the future from Eaton or any other supplier
- The HotSwap MBP 3000 VA is available with different output connectors: French, British, IEC or terminal blocks (Hard-Wired version).
- When used with a 9PX or 9SX the HotSwap MBP 6000 VA and above are providing information on the Bypass status through the UPS LCD screen.
- HotSwap MBP units can be installed as required; at the back, side, top of the UPSs, or rack-mounted.

TECHNICAL CHARACTERISTICS

Brand : EATON

Part number : EFLX8F

Design :

Type : Single-phase

Caractéristiques :

Certification : CE

AC input frequency : 50/60 Hz
AC outlet types : Type E
AC outlets quantity : 9 AC outlet(s)
Cable colour : Black
Depth : 80 mm
Dimensions (WxDxH) : 483 x 80 x 44 mm
Form factor : Rackmount
Height : 44 mm
Load capacity : 3000 VA
Master AC outlets quantity : 8
Maximum current : 13 A
Maximum input current per phase : 13 A
Maximum power : 3000 W
Mounting : Horizontal/Vertical
Nominal input voltage : 230 V
Nominal output voltage : 230 V
Operating temperature (T-T) : 0 - 45 °C
Output connections : 8 x Type E
Package weight : 9.5 kg
PDU types : Basic
Power plug : C20 coupler
Product colour : Black
Rack capacity : 1U
Rack mount kit : Y
Rack mounting : Y
Sustainability certificates : RoHS
Weight : 1.6 kg
Width : 483 mm