

N300 wireless poe ceiling/wall mount access point



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : TP-LINK
Part number : EAP115-WALL
Caractéristiques :
5 GHz : N
2:4 GHz : Y
Antenna gain level (max) : 1.8 dBi
Antenna type : Internal
Antennas quantity : 2
Automatic channel selection : Y
Cable lock slot : N
Cabling technology : 10/100Base-T(X)
Depth : 30.2 mm
Ethernet LAN (RJ-45) ports : 2
Ethernet LAN data rates : 10,100 Mbit/s
Harmonized System (HS) code : 85176990
Height : 86.8 mm
LED indicators : Y
MAC address filtering : Y
Management protocols : SNMP, Telnet
Maximum data transfer rate : 300 Mbit/s
Maximum data transfer rate (2:4 GHz) : 300 Mbit/s
Networking standards : IEEE 802.11a, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.3, IEEE 802.3af, IEEE 802.3u
Number of SSID supported : 8
Operating relative humidity (H-H) : 10 - 90%
Operating temperature (T-T) : 0 - 40 °C
Placement : Wall
Power consumption (typical) : 2.8 W

Power over Ethernet (PoE) : Y
Product colour : White
Quality of Service (QoS) support : Y
Rate limiting : Y
Reset button : Y
Security algorithms : 802.1x RADIUS, HTTPS, WPA, WPA-PSK, WPA2, WPA2-PSK
Storage relative humidity (H-H) : 5 - 90%
Storage temperature (T-T) : -40 - 70 °C
Transmitting power : 15 dBmW
Web-based management : Y
Width : 86.8 mm
Wi-Fi Multimedia (WMM)/(WME) : Y
Wireless isolation : Y