

4K usb hdmi single display kvm over ip extender



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : ATEN
Part number : KE9952T-AX
Caractéristiques :
Type : Transmitter
Certification : RoHS
AC adapter output voltage : 48 V
Cable types supported : Cat5e
Cables included : DisplayPort, USB
Colour depth : 36 bit
Connectivity technology : Wired
Harmonized System (HS) code : 84733080
LED indicators : Y
Manual : Y
Master (outer) case gross weight : 6.21 kg
Master (outer) case height : 232 mm
Master (outer) case length : 427 mm
Master (outer) case net weight : 4.2 kg
Master (outer) case width : 370 mm
Material : Metal
Maximum digital resolution : 3840 x 2160 pixels
Maximum transfer distance : 10000 m
Number of displays supported : 1
Operating relative humidity (H-H) : 0 - 95%
Operating temperature (T-T) : 0 - 50 °C
Package depth : 414 mm
Package height : 117 mm
Package weight : 1.84 kg

Package width : 207 mm
PC Audio in : Y
PC Audio out : Y
Power consumption (transmitter) (max) : 11.88 W
Product colour : Black
Products per master (outer) case : 3 pc(s)
Rack mounting : Y
RJ-45 ports quantity (transmitter) : 1
RS-232 ports : 1
Storage temperature (T-T) : -20 - 60 °C
Transmitter depth : 16.3 cm
Transmitter height : 4.18 cm
Transmitter local keyboard/mouse port type : USB
Transmitter video port type : DisplayPort
Transmitter weight : 1.15 kg
Transmitter width : 21.5 cm
Weight : 1.4 kg