

Eaton 93PS, 10kW frame, 10kW, avec chaine de 32 batteries de 9 Ah, avec MBS



DESCRIPTION

Lowest total cost of ownership and maximum availability taking scalability, resiliency, safety, and efficiency to the next level.

The most advanced UPSs in their power range, the Eaton 91PS and 93PS are ideal for small data centers and other mission - critical applications where efficiency, reliability, safety and scalability are essential.

TECHNICAL CHARACTERISTICS

Brand : EATON
Part number : 91PS10MBSI
Design :
Certification : IEC 62040-1 IEC 62040-2 IEC 62040-3
Battery capacity : 9 Ah
Battery life (max) : 5 year(s)
Battery technology : Sealed Lead Acid (VRLA)
Battery voltage : 12 V
Depth : 750 mm
Efficiency : 96%
Form factor : Tower
Height : 950 mm
Input current Total Harmonic Distortion (THD) : 5%
Input frequency : 50/60 Hz
Input operation voltage (max) : 415 V
Input operation voltage (min) : 220 V
Input power factor : 0.99
International Protection (IP) code : IP20
LED indicators : Y
Noise level : 54 dB
Number of battery cells : 192
Number of input phases : 1/3
Operating altitude : 0 - 2000 m
Output power : 10000 W

Output power capacity : 10 kVA
Output power factor : 1
Output voltage Total Harmonic Distortion (THD) : 1.5%
Power factor : 1
Product colour : Black
Serial interface : Y
Serial interface type : RS-232
Serial ports quantity : 1
UPS topology : Double-conversion (Online)
USB port : Y
Waveform : Sine
Weight : 158 kg
Width : 335 mm