

HANWHA- Camera XNV-6081RE



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : HANWHA
Part number : XNV-6081RE
Représentation / réalisation :
Type : IP security camera
Active tampering alarm : Y
Alarm input/output : Y
Alert notification type : E-mail
Angle of rotation : 355°
Anti-flicker : Y
Audio formats supported : AAC-LC, ADPCM, G.711 -law, G.726
Auto-tracking : Y
Back Light Compensation (BLC) : Y
Bit rate control : Constant Bit Rate (CBR)/Variable Bit Rate (VBR)
Built-in microphone : Y
Camera pan control : Y
Camera shutter speed : 2 - 1/12000 s
Camera shutter type : Electronic
Camera tilt control : Y
Card reader integrated : Y
Closest focusing distance : 0.5 m
Compatible memory cards : MicroSD (TransFlash), MicroSDHC, MicroSDXC
Composite video out : 1
Connectivity technology : Wired
Day/night mode : Y
Detect distance (tele) : 155 m
Detect distance (wide) : 22.4 m
Diameter : 18 cm

Ethernet LAN : Y
Ethernet LAN (RJ-45) ports : 1
Flash memory : 256 MB
Flip & mirror : Y
Focal length range : 2.8 - 12 mm
Focus : Motorized
Fog proof : Y
Form factor : Dome
Frame rate : 60 fps
Height : 125 mm
Highlight Compensation (HLC) : Y
Housing material : Aluminium
HTTPS encryption : Y
Identify distance (tele) : 15 m
Identify distance (wide) : 2.2 m
IK code : IK10+
Image stabilizer : Y
Infrared (IR) cut-off filter : Y
International Protection (IP) code : IP66, IP67, IP69K
IP address filtering : Y
LED type : IR
Lens viewing angle, diagonal : 142.1°
Lens viewing angle, horizontal : 119.5°
Lens viewing angle, vertical : 62.8°
Mac operating systems supported : Mac OS X 10.13 High Sierra
Maximum aperture number : 3.6
Maximum memory card size : 512 GB
Maximum resolution : 1920 x 1080 pixels
Microphone in : Y
Minimum aperture number : 1.4
Minimum illumination : 0.015 lx
Mirror : Y
Motion sensor : Y
Mounting type : Ceiling
Networking standards : IEEE 802.3af
Night vision : Y
Night vision distance : 50 m
Noise reduction : Y
Number of cameras : 1
Number of effective pixels (H x V) : 1945 x 1097 pixels
Number of lenses : 1
Number of sensors : 1
Number of users : 20 user(s)
Observe distance (tele) : 62 m
Observe distance (wide) : 9 m
Operating relative humidity (H-H) : 0 - 90%
Operating temperature (T-T) : -40 - 55 °C
Optical sensor size : 25.4 / 2.8 mm (1 / 2.8»)
Optical zoom : 4.3x
Pan range : 0 - 360°
Placement supported : Indoor & outdoor
Power consumption (max) : 25.5 W
Power consumption (Power over Ethernet (PoE)) : 12.95 W

Power consumption (typical) : 10.2 W
Power source type : AC, PoE
Privacy masking : Y
Product colour : White
Progressive scan : Y
Quality of Service (QoS) support : Y
Recognize distance (tele) : 31 m
Recognize distance (wide) : 4.5 m
Remote viewing : Y
Sample rate : 16 kHz
Security algorithms : EAP-LEAP, EAP-TLS, HTTPS
Sensor type : CMOS
Storage relative humidity (H-H) : 0 - 90%
Storage temperature (T-T) : -50 - 60 °C
Streaming method : Multicast, Unicast
Supported graphics resolutions : 320 x 240, 640 x 360, 640 x 480 (VGA), 720 x 480, 720 x 576, 800 x 448, 800 x 600 (SVGA), 1024 x 768 (XGA), 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1280 x 960, 1920 x 1080 (HD 1080)
Supported network protocols : IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP,RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2)
Tilt angle range : -45 - 85°
Total megapixels : 2 MP
USB port : Y
Video compression formats : H.264, H.265, M-JPEG
Video formats supported : H.264, H.265, M-JPEG
Video intelligence analytic : Y
Video motion detection : Y
&em