

HANWHA- Camera PNM-C34404RQPZ



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : HANWHA
Part number : PNM-C34404RQPZ
Représentation / réalisation :
Type : IP security camera
Angle of rotation : 90°
Back Light Compensation (BLC) : Yes
Camera shutter type : Electronic
Card reader integrated : Yes
Compatible memory cards : MicroSD (TransFlash), MicroSDHC, MicroSDXC
Connectivity technology : Wired
Day/night mode : Yes
Diameter : 38 cm
Dynamic range : 120 dB
Ethernet interface type : Gigabit Ethernet
Ethernet LAN : Yes
Flip & mirror : Yes
Focal length range : 3.3 - 5.7 mm
Form factor : Dome
Frame rate : 20 fps
Height : 301.9 mm
Housing material : Aluminium
IK code : IK10
International Protection (IP) code : IP66
Languages support : Czech, German, Dutch, English, Spanish, French, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Turkish
LED type : IR
Maximum aperture number : 1.9
Maximum memory card size : 1.02 TB

Maximum resolution : 3840 x 2160 pixels
Minimum illumination : 0.01 lx
Mirror : Yes
Mounting type : Ceiling
Night vision : Yes
Night vision distance : 20 m
Number of cameras : 1
Number of effective pixels (H x V) : 3840 x 2160 pixels
Operating relative humidity (H-H) : 0 - 95%
Operating temperature (T-T) : -40 - 50 °C
Optical sensor size : 25.4 / 2.8 mm (1 / 2.8»)
Pan range : 0 - 360°
Placement supported : Indoor & outdoor
Power consumption (max) : 64 W
Power consumption (typical) : 45 W
Power source type : PoE
Privacy masking : Yes
Product colour : Black, White
PTZ control : Yes
Sensor type : CMOS
Storage relative humidity (H-H) : 0 - 95%
Storage temperature (T-T) : -50 - 60 °C
Supported graphics resolutions : 640 x 360, 640 x 480 (VGA), 720 x 480, 720 x 576, 800 x 448, 800 x 600 (SVGA), 1024 x 768 (XGA), 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1280 x 960, 1920 x 1080 (HD 1080), 3840 x 2160
Supported network protocols : IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, UPnP, Bonjour, LLDP, SRTP(TCP, UDP Unicast), MQTT
Tilt angle range : 9 - 65°
Total megapixels : 2 MP
Video compression formats : H.264, H.265, M-JPEG
Video streaming : Yes
Weight : 7.9 kg
White balance : ATW, AWC, Indoor, Manual, Outdoor
Wide Dynamic Range (WDR) : Yes