



## DESCRIPTION

## TECHNICAL CHARACTERISTICS

Brand : PHILIPS

Part number : 43BDL4511D/00

### Connectivité :

RS-232C : Y

### Certificat :

Certification : CE FCC Class A CCC Restriction of Hazardous Substances (ROHS) CB BSMI EMF VCCI PSB ETL CECP EAC Energy Star 8.0

AC input frequency : 50/60 Hz

AC input voltage : 100/240 V

Audio (L/R) in : 1

Audio (L/R) out : 1

Audio formats supported : AAC, HE-AAC

Base width : 56.1 cm

Batteries included : Y

Built-in speaker(s) : Y

Cables included : AC, IR sensor, RS-232

Contrast ratio (dynamic) : 500000:1

Contrast ratio (typical) : 1200:1

Depth : 63.5 mm

Display brightness : 500 cd/m<sup>2</sup>

Display depth : 63.5 mm

Display diagonal : 109.2 cm (43»)

Display diagonal (metric) : 108 cm

Display height : 561.2 mm

Display number of colours : 1.07 billion colours

Display resolution : 3840 x 2160 pixels

Display weight : 10.7 kg

Display width : 973 mm

DisplayPorts in : 1  
DisplayPorts out : 1  
DisplayPorts quantity : 2  
DVI port : Y  
DVI-I ports quantity : 1  
Energy efficiency class (SDR) : G  
Ethernet LAN : Y  
Ethernet LAN (RJ-45) ports : 1  
HD type : 4K Ultra HD  
HDMI ports quantity : 3  
HDMI version : 2.0  
Image formats supported : BMP, JPEG, PNG  
Maximum refresh rate : 60 Hz  
Native aspect ratio : 16:9  
Number of built-in speakers : 2  
On Screen Display (OSD) : Y  
On Screen Display (OSD) languages : Arabic  
Operating hours (hours/days) : 24/7  
Operating relative humidity (H-H) : 20 - 80%  
Operating temperature (T-T) : 0 - 40 °C  
OPS module slot : Y  
Panel life : 50000 h  
Panel mounting interface : 200 x 200 mm  
Pixel pitch : 0.2451 x 0.2451 mm  
Placement supported : Indoor  
Power consumption (max) : 170 W  
Power consumption (standby) : 0.5 W  
Power consumption (typical) : 62 W  
Product colour : Black  
Product design : Digital A-board  
Purpose : Commercial  
Remote (IR) input : 1  
Remote (IR) output : 1  
Remote control included : Y  
Response time : 8 ms  
RMS rated power : 10 W  
Storage relative humidity (H-H) : 5 - 95%  
Storage temperature (T-T) : -20 - 60 °C  
USB port : Y  
USB ports quantity : 2  
USB version : 2.0  
VESA mounting : Y  
Video formats supported : H.263, H.264, H.265, MPEG  
Viewing angle, horizontal : 178°  
Viewing angle, vertical : 178°  
Weight : 10.7 kg  
Width : 973 mm