

HANWHA- Camera QNV-6082R1



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : HANWHA
Part number : QNV-6082R1
Représentation / réalisation :
Type : IP security camera
Réseau :
Bluetooth : N
Système d'objectif :
Auto focus : Y
Alarm input channels : 1
Alarm input/output : Y
Alarm output channels : 1
Angle of rotation : 355°
Anti-flicker : Y
Back Light Compensation (BLC) : Y
Bit rate control : Constant Bit Rate (CBR), Constant Bit Rate (CBR)/Variable Bit Rate (VBR), Variable Bit Rate (VBR)
Built-in HDD : N
Compatible memory cards : SD, SDHC, SDXC
Connectivity technology : Wired
Day/night mode : Y
DC output voltage : 12
DC-in jack : Y
Detect distance (tele) : 128.8 m
Detect distance (wide) : 27.4 m
Diameter : 13.7 cm
Digest authentication : Y
Dynamic range : 120 dB
Ethernet LAN : Y

Ethernet LAN (RJ-45) ports : 1
Flash memory : 256 MB
Flip & mirror : Y
Focal length range : 3.2 - 10 mm
Form factor : Dome
Frame rate : 30 fps
Gain control type : Auto
Height : 106.1 mm
Identify distance : 12.9 m
Identify distance (tele) : 12.9 m
Identify distance (wide) : 2.7 m
IK code : IK10
Internal memory : 512 MB
International Protection (IP) code : IP66
IP address filtering : Y
LED type : IR
Maximum aperture number : 1.6
Maximum memory card size : 128 GB
Maximum resolution : 1920 x 1080 pixels
Minimum illumination : 0.03 lx
Mirror : Y
Mounting type : Ceiling
Night vision : Y
Noise reduction : Y
Number of cameras : 1
Number of lenses : 1
Number of sensors : 1
Number of users : 6 user(s)
Observe distance (tele) : 51.5 m
Observe distance (wide) : 11 m
Operating relative humidity (H-H) : 0 - 90%
Operating temperature (T-T) : -30 - 55 °C
Optical sensor size : 25.4 / 2.8 mm (1 / 2.8»)
Pan range : 0 - 350°
Placement supported : Indoor & outdoor
Power consumption (max) : 7.7 W
Power consumption (Power over Ethernet (PoE)) : 7.7 W
Power source type : DC, PoE
Privacy masking : Y
Product colour : White
Quality of Service (QoS) support : Y
Recognize distance (tele) : 25.8 m
Recognize distance (wide) : 5.5 m
Security algorithms : EAP-LEAP, EAP-TLS, HTTPS
Sensor type : CMOS
Storage relative humidity (H-H) : 0 - 90%
Storage temperature (T-T) : -30 - 60 °C
Streaming method : Multicast, Unicast
Supported graphics resolutions : 640 x 360, 640 x 480 (VGA), 720 x 480, 720 x 576, 800 x 448, 800 x 600 (SVGA), 1280 x 720 (HD 720), 1280 x 960, 1920 x 1080 (HD 1080)
Supported network protocols : IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, UPnP, Bonjour, LLDP
Tilt angle range : 0 - 67°

Total megapixels : 2 MP
Video compression formats : H.264, H.265, M-JPEG
Video motion detection : Y
Video streaming : Y
Weight : 710 g
White balance : ATW, AWC, Indoor, Manual, Outdoor
Wide Dynamic Range (WDR) : Y
Wi-Fi : N