



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : DAHUA TECHNOLOGY

Part number : DH-SD5A432GB-HNR

Représentation / réalisation :

Type : IP security camera

Réseau :

Bluetooth : No

Système d'objectif :

Auto focus : Yes

Certification : CE: EN55032/EN55024/EN50130-4 FCC: Part15 subpartB, ANSI C63.4-2014 UL: UL60950-1+CAN/CSA C22.2, No.60950-1

Audio formats supported : G.711, G.722.1, G.723, G.726, G.729

Auto-tracking : Yes

Back Light Compensation (BLC) : Yes

Built-in HDD : No

Closest focusing distance : 0.8 m

Compatible memory cards : MicroSD (TransFlash)

Connectivity technology : Wired

DC output current : 2.5 A

DC output voltage : 24

Detect distance : 2124 m

Diameter : 19 cm

Digital Wide Dynamic Range (DWDR) : Yes

Digital zoom : 16x

Ethernet LAN : Yes

Ethernet LAN (RJ-45) ports : 1

Focal length range : 4.8154

Focus : Manual

Form factor : Turret

Headphone outputs : 1
Height : 332 mm
Identify distance : 212 m
IK code : IK10
Internal memory : 1000 MB
International Protection (IP) code : IP67
LED type : IR
Lens viewing angle, diagonal : 67.53.2
Lens viewing angle, horizontal : 58.52.8
Lens viewing angle, vertical : 31.91.3
Maximum aperture number : 4
Maximum memory card size : 512 GB
Maximum resolution : 2560 x 1440 pixels
Minimum aperture number : 1.6
Minimum illumination : 0.0005 lx
Mounting type : Ceiling
Night vision : Yes
Night vision distance : 150 m
Noise reduction : Yes
Noise reduction technology : 2D noise reduction, 3D noise reduction
Number of cameras : 1
Number of illumination LEDs : 4
Number of lenses : 1
Observe distance : 839 m
Operating relative humidity (H-H) : 0 - 95%
Operating temperature (T-T) : -40 - 70 °C
Optical sensor size : 25.4 / 2.8 mm (1 / 2.8»)
Optical zoom : 32x
Package weight : 8 kg
Pan manual speed : 0.1 - 300 °/sec
Pan preset speed : 400 °/sec
Pan range : 0 - 360°
Placement supported : Indoor & outdoor
Power consumption (max) : 22 W
Power consumption (typical) : 13 W
Power source type : DC, PoE
Product colour : Black, White
PTZ control : Yes
PTZ modes : 5 Pattern
Recognize distance : 425 m
ROM capacity : 4000 MB
Sensor type : CMOS
Supported graphics resolutions : 352 x 240, 352 x 288, 704 x 480, 704 x 576, 1280 x 720 (HD 720), 1920 x 1080 (HD 1080), 2048 x 1536 (QXGA), 2560 x 1440
Supported network protocols : HTTP; HTTPS; IPv4; RTSP; UDP; SMTP; NTP; DHCP; DNS; DDNS; IPv6; 802.1x; QoS; FTP; UPnP; ICMP; SNMP; SNMP v1/v2c/v3 (MIB-2); IGMP; ARP; RTCP; RTP; PPPoE; RTMP; TCP
Tilt angle range : 15 - 90°
Tilt manual speed : 0.1 - 200 °/sec
Tilt preset speed : 300 °/sec
Total megapixels : 4 MP
Video compression formats : H.264, H.264+, H.264B, H.264H, H.265, H.265+
Web browser : Yes
Web-based management : Yes
Weight : 4.7 kg

White balance : Auto, Indoor, Manual, Natural, Outdoor, Sodium lamp, Street lamp

Wi-Fi : No

Zoom capability : Yes