

HANWHA- Camera 4K PNV-A9081RLP



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : HANWHA	
Part number : PNV-A9081RLP	
Représentation / réalisation :	
Type :	IP security camera
Alert notification type :	E-mail
Camera shutter speed :	1/5~1/12000 s
Camera shutter type :	Electronic
Connectivity technology :	Wired
Day/night mode :	Y
DC output voltage :	12
Detect distance (tele) :	183 m
Detect distance (wide) :	62.9 m
Diameter :	18 cm
Ethernet LAN :	Y
Ethernet LAN (RJ-45) ports :	1
Flash memory :	512 MB
Form factor :	Dome
Height :	125 mm
Housing material :	Aluminium
HTTPS encryption :	Y
Identify distance (tele) :	18.3 m
Identify distance (wide) :	6.3 m
IK code :	IK10+
Internal memory :	4096 MB
International Protection (IP) code :	IP66, IP67, IP69K
IP address filtering :	Y
Languages support :	Simplified Chinese, Czech, German, Dutch, English, Spanish, French, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Rus-

sian, Swedish, Turkish
Maximum aperture number : 2.65
Maximum resolution : 3840 x 2160 pixels
Minimum aperture number : 1.6
Mounting type : Ceiling
Number of cameras : 1
Number of languages : 17
Number of lenses : 1
Observe distance (tele) : 73.3 m
Observe distance (wide) : 25.1 m
Operating relative humidity (H-H) : 0 - 90%
Operating temperature (T-T) : -40 - 55 °C
Optical sensor size : 25.4 / 1.8 mm (1 / 1.8»)
Pan range : 0 - 360°
Placement supported : Outdoor
Power consumption (Power over Ethernet (PoE)) : 20 W
Power source type : DC, PoE
Product colour : White
Recognize distance (tele) : 36.6 m
Recognize distance (wide) : 12.6 m
Security algorithms : EAP-LEAP, EAP-TLS, HTTPS, SSL/TLS
Sensor type : CMOS
Storage relative humidity (H-H) : 0 - 90%
Storage temperature (T-T) : -50 - 60 °C
Streaming method : Multicast, Unicast
Supported graphics resolutions : 640 x 360, 720 x 576, 800 x 600 (SVGA), 1024 x 768 (XGA), 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1280 x 960, 1600 x 1200 (UXGA), 1920 x 1080 (HD 1080), 2048 x 1536 (QXGA), 2560 x 1440, 3072 x 1728, 3840 x 2160
Supported network protocols : IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP,RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, UPnP, Bonjour, LLDP, SRTP (TCP, UDP Unicast)
Tilt angle range : -45 - 85°
User access level : User
Video intelligence analytic : Y
Weight : 1.9 kg
White balance : ATW, AWC, Indoor, Manual, Outdoor