

HANWHA- Camera box IP XNB-9002



DESCRIPTION

Wisenet X powered by Wisenet 7 network box camera, easy access to all ports, 4K @30fps, H.265/H.264/MJPEG, WiseStream II compression technology, extremeWDR, USB port for easy installation, advanced video analytics and sound classification, true D/N, dual SD card slots, hallway view, HLC, defocus detection, defog detection, DIS, 12VDC/24VAC/PoE. Advanced cybersecurity built-in.

TECHNICAL CHARACTERISTICS

Brand : HANWHA
Part number : XNB-9002
Représentation / réalisation :
Type : IP security camera
Réseau :
Bluetooth : N
AC input voltage : 24 V
Alarm input/output : Y
Back Light Compensation (BLC) : Y
Bit rate control : Constant Bit Rate (CBR)/Variable Bit Rate (VBR)
Built-in HDD : N
Camera shutter speed : 1/5-1/12000 s
Camera shutter type : Electronic
Card reader integrated : Y
Compatible memory cards : MicroSD (TransFlash), MicroSDHC, MicroSDXC
Composite video out : 1
Connectivity technology : Wired
Day/night mode : Y
DC output voltage : 12
Depth : 165 mm
Ethernet interface type : Gigabit Ethernet
Ethernet LAN : Y
Flash memory : 512 MB
Flip & mirror : Y
Form factor : Box

Frame rate : 30 fps
Height : 67 mm
Highlight Compensation (HLC) : Y
Housing material : Aluminium
HTTPS encryption : Y
Infrared (IR) cut-off filter : Y
Intelligent Video Surveillance (IVS) system features : Defocus, People counting
Internal memory : 4000 MB
IP address filtering : Y
Maximum memory card size : 256 GB
Maximum resolution : 3840 x 2160 pixels
Minimum illumination : 0.005 lx
Mounting type : Ceiling/wall
Networking standards : IEEE 802.1x, IEEE 802.3af
Number of cameras : 1
Number of sensors : 1
Number of users : 20 user(s)
Operating relative humidity (H-H) : 0 - 95%
Operating temperature (T-T) : -10 - 55 °C
Optical sensor size : 25.4 / 2.8 mm (1 / 2.8»)
Placement supported : Indoor
Power consumption (max) : 13.5 W
Power consumption (Power over Ethernet (PoE)) : 12.95 W
Power source type : AC, DC, PoE
Product colour : Black
Quality of Service (QoS) support : Y
Security algorithms : EAP-LEAP, EAP-TLS, HTTPS, SSL/TLS
Sensor type : CMOS
Storage relative humidity (H-H) : 0 - 90%
Storage temperature (T-T) : -50 - 60 °C
Streaming method : Multicast, Unicast
Supported network protocols : IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP,RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, UPnP, Bonjour, LLDP, SRTP (TCP, UDP Unicast)
Video compression formats : H.264, H.265, M-JPEG
Video motion detection : Y
Video streaming : Y
Voice codecs : G.711, G.711ulaw, G.726
Weight : 880 g
White balance : ATW, AWC, Indoor, Manual, Outdoor
Wide Dynamic Range (WDR) : Y
Width : 81 mm
Wi-Fi : N