

OPTOMA- Projector ZH450



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : OPTOMA
Part number : E9PD7L321EZ1
Vidéo :
Full HD : Y
Caractéristiques :
Certification : IP6X
3D : Y
AC adapter included : Y
AC input frequency : 50/60 Hz
AC input voltage : 100 - 240 V
Analog signal format system : NTSC 3.58, NTSC 4.43, NTSC J, NTSC M, PAL 4.43, PAL B, PAL G, PAL H, PAL I, PAL M, PAL N, SECAM 4.25/4.4, SECAM B, SECAM D, SECAM G, SECAM K, SECAM K1, SECAM L
Auto power off : Y
Battery type : CR2025
Built-in speaker(s) : Y
Cable lock slot : Y
Cable lock slot type : Kensington
Card reader integrated : N
Contrast ratio (dynamic) : 2000000:1
Contrast ratio (typical) : 300000:1
DC-in jack : Y
Depth : 216 mm
Doesn't contain : Mercury
DVI port : N
Focal length range : 20.91 - 32.62 mm
HDMI connector type : Full-size
HDMI ports quantity : 2

HDMI version : 2.0
Headphone outputs : 1
Height : 114 mm
Horizontal scan range : 15 - 140 kHz
Interactive : N
Keystone correction, horizontal : -30 - 30°
Keystone correction, vertical : -30 - 30°
Light source type : Laser
Manual : Y
Market positioning : Presentation
Native aspect ratio : 16:9
Noise level : 29 dB
Number of colours : 1.073 billion colours
Number of OSD languages : 26
Offset : 116%
On Screen Display (OSD) languages : Arabic, Simplified Chinese, Traditional Chinese, Czech, Danish, German, Dutch, English, Spanish, French, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Swedish, Turkish, Vietnamese
Operating altitude : 0 - 2500 m
Operating temperature (T-T) : 0 - 40 °C
Package weight : 4.2 kg
Password protection : Y
Power consumption (economy mode) : 119 W
Power consumption (max) : 173 W
Power consumption (standby) : 0.5 W
Power source : AC
Product colour : White
Product type : Standard throw projector
Projection distance : 1 - 10 m
Projection technology : DLP
Projector brightness : 4500 ANSI lumens
Projector native resolution : 1080p (1920x1080)
Quantity per pack : 1 pc(s)
Remote control included : Y
RMS rated power : 15 W
Screen size compatibility : 508 - 8178.8 mm (20 - 322»)
Serial interface type : RJ-45, RS-232
Service life of light source : 30000 h
Supported aspect ratios : 4:3, 16:10, 16:9
Supported graphics resolutions : 640 x 480 (VGA), 800 x 600 (SVGA), 1024 x 768 (XGA), 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1280 x 800 (WXGA), 1600 x 1200 (UXGA), 1920 x 1080 (HD 1080)
Supported video modes : 480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Throw ratio : 1.4:1 ~ 2.24:1
Uniformity : 75%
USB 2.0 ports quantity : 1
USB 2.0 Type-A ports quantity : 1
Vertical scan range : 24 - 120 Hz
Weight : 3 kg
Width : 274 mm
Zoom capability : Y
Zoom ratio : 1.6:1
Zoom type : Manual