

SONY- Projector VPL-FHZ85- White



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : SONY

Part number : VPL-FHZ85

Vidéo :

Full HD : Y

3D : N

AC input frequency : 50 - 60 Hz

AC input voltage : 100 - 240 V

Analog signal format system : NTSC 3.58, NTSC 4.43, PAL, PAL 60, PAL M, PAL N, SECAM

Built-in display : N

Built-in speaker(s) : N

Card reader integrated : N

Component video (YPbPr/YCbCr) in : 1

Composite video in : 1

Contrast ratio (typical) : 8000:1

Depth : 169 mm

DVI port : Y

Ethernet LAN : Y

Ethernet LAN (RJ-45) ports : 1

Focus : Auto

Harmonized System (HS) code : 85286200

HDMI ports quantity : 1

Height : 494 mm

Keystone correction, horizontal : 30°

Keystone correction, vertical : 30°

Light source type : Laser

Market positioning : Portable

Native aspect ratio : 16:9

Noise level : 36 dB
Noise level (economic mode) : 34 dB
Operating relative humidity (H-H) : 35 - 85%
Operating temperature (T-T) : 0 - 45 °C
PC Audio in : Y
PC in (D-Sub) : Y
Power consumption (standby) : 0.3 W
Power consumption (typical) : 397 W
Power source : DC
Product colour : White
Product type : Large venue projector
Projection technology : 3LCD
Projector brightness : 8000 ANSI lumens
Projector native resolution : WUXGA (1920x1200)
Screen size compatibility : 1016 - 15240 mm (40 - 600»)
Serial interface type : RS-232C
Service life of light source : 20000 h
Smart projector : Y
Storage relative humidity (H-H) : 10 - 90%
Storage temperature (T-T) : -10 - 60 °C
Supported graphics resolutions : 1920 x 1200 (WUXGA)
Supported video modes : 480p, 576p, 720p, 1080i, 1080p
S-Video inputs quantity : 1
Throw ratio : 1.39:1 - 2.23:1
VGA (D-Sub) ports quantity : 1
Weight : 13 kg
Width : 460 mm
Zoom capability : Y
Zoom ratio : 1.6:1
Zoom type : Auto/Manual