

HANWHA- Camera XNF-9013RV



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : HANWHA

Part number : XNF-9013RV

Représentation / réalisation :

Type : IP security camera

Réseau :

Bluetooth : No

Alarm input/output : Yes

Anti-flicker : Yes

Audio detection : Yes

Audio formats supported : AAC-LC, ADPCM, G.711 -law, G.726

Audit log : Yes

Back Light Compensation (BLC) : Yes

Bit rate control : Constant Bit Rate (CBR)/Variable Bit Rate (VBR)

Built-in HDD : No

Camera shutter speed : 1/5 - 1/12000 s

Camera shutter type : Electronic

Card reader integrated : Yes

Closest focusing distance : 0.5 m

Compatible memory cards : MicroSD (TransFlash), MicroSDHC, MicroSDXC

Connectivity technology : Wired

Day/night mode : Yes

DC output voltage : 12

Detect distance : 34.9 m

Diameter : 16 cm

Ethernet interface type : Fast Ethernet

Ethernet LAN : Yes

Ethernet LAN (RJ-45) ports : 1

Field of view (FOV) angle : 187°
Fixed focal length : 1.08 mm
Flash memory : 512 MB
Flip & mirror : Yes
Form factor : Dome
Frame rate : 30 fps
Gain control type : Manual
Height : 72 mm
Highlight Compensation (HLC) : Yes
Housing material : Aluminium
HTTPS encryption : Yes
Identify distance : 3.5 m
IK code : IK10
Intelligent Video Surveillance (IVS) system features : Defocus, Face detection, Human detection, Vehicle detection
International Protection (IP) code : IP66
IP address filtering : Yes
LED type : IR
Maximum memory card size : 512 GB
Maximum resolution : 3008 x 3008 pixels
Minimum aperture number : 2.2
Mounting type : Ceiling/wall
Night vision : Yes
Night vision distance : 13 m
Noise reduction : Yes
Noise reduction technology : Smart Super Noise Reduction V (SSNR V), WiseNR
Number of cameras : 1
Number of lenses : 1
Number of Privacy masking areas : 32
Number of sensors : 1
Number of users : 20 user(s)
Observe distance : 13.9 m
Operating relative humidity (H-H) : 0 - 95%
Operating temperature (T-T) : -40 - 60 °C
Optical sensor size : 25.4 / 2.3 mm (1 / 2.3»)
People counting function : Yes
Placement supported : Indoor & outdoor
Power consumption (max) : 22 W
Power consumption (Power over Ethernet (PoE)) : 9.4 W
Power consumption (typical) : 9 W
Power source type : DC, PoE
Product colour : White
PTZ control : Yes
RAM capacity : 4096 MB
Recognize distance : 7 m
Security algorithms : EAP-LEAP, EAP-TLS, HTTPS
Sensor type : CMOS
Storage temperature (T-T) : -50 - 60 °C
Streaming method : Multicast, Unicast
Supported network protocols : IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP,RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, UPnP, Bonjour, LLDP, SRTP (TCP, UDP Unicast)
Total megapixels : 12 MP
USB port : Yes
Video compression formats : H.264, H.265, M-JPEG

Video motion detection : Yes

Video streaming : Yes

Weight : 1.17 kg

White balance : ATW, AWC, Indoor, Manual, Outdoor

Wide Dynamic Range (WDR) : Yes

Wi-Fi : No