



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : LEGRAND
Part number : 311072
AC outlet types : C13 coupler, C19 coupler
AC outlets quantity : 9 AC outlet(s)
Auto shut-off : Y
Depth : 600 mm
Display type : LCD
Efficiency : 85%
Efficiency (ECO mode) : 98%
Emergency Power Off (EPO) : Y
Form factor : Rackmount
Height : 88 mm
Input frequency : 47/63 Hz
Input operation voltage (max) : 288 V
Input operation voltage (min) : 175 V
Management protocols : Network management,Simple Network Management Protocol (SNMP)
Number of output phases : 1
Output frequency : 50/60 Hz
Output operation voltage (max) : 240 V
Output operation voltage (min) : 208 V
Output power : 2700 W
Output power capacity : 3 kVA
Output power factor : 0.9
Output voltage Total Harmonic Distortion (THD) : 3%
Potential-free output : Y
Power factor : 0.9
Power plug : C20 coupler

Power source type : AC
Product colour : Black
Products per master (outer) case : 1 pc(s)
Rack capacity : 2U
RS-232 ports : 1
Serial interface : N
Typical backup time at full load : 0.00016 min
UPS topology : Line-Interactive
USB port : Y
Waveform : Sine
Weight : 29.5 kg
Width : 440 mm