

BOSCH NIN-73013-A3A



DESCRIPTION

NIN-73023-A3A Dome 2MP HDR 3-9mm auto IP66

- Excellent low-light performance
- Built-in Intelligent Video Analytics to trigger relevant alerts and quickly retrieve data
- Intelligent Dynamic Noise Reduction reduces bandwidth and storage requirements by up to 50%
- Extended Dynamic Range mode to see details in bright and dark areas simultaneously
- Easy to install with auto zoom/focus SR lens, wizard and pre-configured modes

TECHNICAL CHARACTERISTICS

Brand : BOSCH

Part number : NIN-73013-A3A

Représentation / réalisation :

Type : IP security camera

Réseau :

Bluetooth : N

Système d'objectif :

Auto focus : Y

Détails techniques :

Iris : Y

Alarm input/output : Y

Analog signal format system : NTSC, PAL

Angle of rotation : 270°

Audio formats supported : G.711, LC-AAC

Audio system full duplex : Y

Auto-tracking : Y

Built-in HDD : N

Cabling technology : 10/100Base-T(X)

Camera pan control : N

Camera shutter type : Electronic

Camera tilt control : N

Compatible memory cards : MicroSDHC, MicroSDXC
Connectivity technology : Wired
Day/night mode : Y
DC output voltage : 48
Depth : 158 mm
Ethernet LAN : Y
Ethernet LAN (RJ-45) ports : 1
Firmware upgradeable : Y
Flip & mirror : Y
Focus : Motorized
Form factor : Dome
Frame rate : 60 fps
Height : 124 mm
Housing material : Aluminium
HTTPS encryption : Y
Image quality adjustment : Brightness, Contrast, Saturation, Sharpness
International Protection (IP) code : IP66
LED indicators : Y
Lens mount interface : Board mount
Lens viewing angle, horizontal : 117°
Lens viewing angle, vertical : 59°
Maximum memory card size : 2000 GB
Maximum resolution : 1920 x 1080 pixels
Minimum illumination : 0.0075 lx
Mounting type : Ceiling
Networking standards : IEEE 802.3af, IEEE 802.3at
Noise reduction : Y
Number of cameras : 1
Number of effective pixels (H x V) : 1280 x 720 pixels
Number of sensors : 1
Operating relative humidity (H-H) : 5 - 93%
Operating temperature (T-T) : -34 - 74 °C
Optical sensor size : 25.4 / 2.8 mm (1 / 2.8»)
Pan range : 0 - 360°
Placement supported : Indoor & outdoor
Power consumption (typical) : 7.2 W
Power over Ethernet (PoE) : Y
Power source type : PoE
Privacy masking : Y
Product colour : Black, White
Protection features : Scratch resistant
Quality of Service (QoS) support : Y
Region of Interest (ROI) encoding : Y
Sample rate : 16 kHz
Security algorithms : SHA-256, 3DES, 802.1x RADIUS, DES, MD5, SHA-1, SNMP
Sensor type : CMOS
Signal-to-Noise Ratio (SNR) : 50 dB
Storage relative humidity (H-H) : 5 - 98%
Storage temperature (T-T) : -50 - 70 °C
Supported graphics resolutions : 256 x 144, 512 x 288, 704 x 480, 768 x 432, 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1920 x 1080 (HD 1080)
Supported video modes : 480p, 720p, 1080p
Tilt angle range : 0 - 90°
Time stamp overlay : Y

Total megapixels : 1 MP

Video compression formats : H.264, M-JPEG

Video streaming : Y

Weight : 850 g

Wi-Fi : N

Zoom capability : Y