

HANWHA- 2 Mps Network Positioning Camera TNU-6321



DESCRIPTION

TECHNICAL CHARACTERISTICS

Brand : HANWHA
Part number : TNU-6321
Représentation / réalisation :
Type : IP security camera
Réseau :
Bluetooth : N
AC input voltage : 24 V
Back Light Compensation (BLC) : Y
Bit rate control : Constant Bit Rate (CBR)/Variable Bit Rate (VBR)
Built-in HDD : N
Card reader integrated : Y
Closest focusing distance : 1.5 m
Compatible memory cards : MicroSD (TransFlash), MicroSDHC, MicroSDXC
Composite video out : 1
Connectivity technology : Wired
Day/night mode : Y
Depth : 460 mm
Ethernet interface type : Fast Ethernet
Ethernet LAN : Y
Ethernet LAN (RJ-45) ports : 1
Flash memory : 256 MB
Focal length range : 4.44 - 142.6 mm
Height : 528.2 mm
Highlight Compensation (HLC) : Y
Housing material : Aluminium
Image stabilizer : Y
Infrared (IR) cut-off filter : Y

Internal memory : 1024 MB
International Protection (IP) code : IP66
Lens viewing angle, horizontal : 61.8°
Lens viewing angle, vertical : 36.2°
Maximum aperture number : 4.4
Maximum memory card size : 256 GB
Maximum resolution : 1920 x 1080 pixels
Minimum aperture number : 1.6
Minimum illumination : 0.005 lx
Mounting type : Ceiling/wall
Noise reduction : Y
Number of cameras : 1
Number of effective pixels (H x V) : 1944 x 1212 pixels
Number of lenses : 1
Number of sensors : 1
Number of users : 20 user(s)
Operating relative humidity (H-H) : 0 - 90%
Operating temperature (T-T) : -40 - 55 °C
Optical sensor size : 25.4 / 2.8 mm (1 / 2.8»)
Optical zoom : 32x
Pan range : 0 - 360°
Placement supported : Outdoor
Power consumption (max) : 100 W
Power source type : AC
Product colour : White
Quality of Service (QoS) support : Y
Sensor type : CMOS
Storage relative humidity (H-H) : 0 - 90%
Storage temperature (T-T) : -40 - 60 °C
Streaming method : Multicast, Unicast
Supported network protocols : IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP,RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, PIM-SM, UPnP, Bonjour, LLDP, SRTP
Tilt angle range : -90 - 40°
Total megapixels : 2 MP
Video compression formats : H.264, H.265, M-JPEG
Video motion detection : Y
Video streaming : Y
Weight : 14 kg
White balance : ATW, AWC, Indoor, Manual, Outdoor
Wide Dynamic Range (WDR) : Y
Width : 219 mm
Wi-Fi : N
Zoom capability : Y